LOW-VOLTAGE PENDANTS

Tetra Pendant



DESCRIPTION

Tall rectilinear glass in frost white accented with four metal beads. Includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAA® module and six feet of field-cuttable suspension cable. Works with SORAA.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system.

ACCESSORIES & OPTICAL CONTROLS


SORAA® LED Bi-Pin Replacement Pendant Module, Swag Hook

WEIGHT

1.25lb / 0.57kg ±



white



white

ORDERING INFORMATION

700 SYSTEM TETW	COLOR	FINISH	LAMP
FJ FREEJACK MP MONOPOINT MO MONORAIL MO2 TWO-CIRCUIT MONORAIL	WHITE	Z ANTIQUE BRONZE C CHROME S SATIN NICKEL	12 VOLT HALOGEN -LEDS830 12 VOLT LED 80 CRI 3000K -24 24 VOLT HALOGEN

Note: MP includes 4" Round Flush Canopy.Note: MP includes 4 Round Flush Canopy.

When installing LED option on MO2 only magnetic transformers may be used.



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

FIXTURE TYPE:
JOB NAME:
NOTES:



©2016 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.