


# LOW-VOLTAGE HEADS

## Envision Head

### DESCRIPTION

Specification grade head with precision internal gearing mechanisms that allow for hot aiming and are self-locking. Rotates 360° and pivots 0° to 90°. Up to two MR16 size lenses or louvers (sold separately) are held captive inside the lamp cartridge which includes an integral glare reducing snoot. Lamp cartridge and lens orientation adjust 180°. Lamp cartridge is keyed to maintain accurate focus during relamping. All functionality can be fine-tuned using a phillips or flat head screwdriver and with the guide of accompanying markings. Low-voltage, MR16 lamp of up to 50 watts (not included).



### INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

### ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

### WEIGHT

1.19lb / 0.54kg ±



back

left

right

### ORDERING INFORMATION

700	SYSTEM	ENV	LENGTH (A)	FINISH	LAMP
FJ	FREEJACK		03 3.5"	S SATIN NICKEL	12 VOLT HALOGEN
MP	MONOPOINT		07 7.5"		
MO	MONORAIL				
MO2	TWO-CIRCUIT MONORAIL				

Note: MP includes 4" Round Flush Canopy.



Tech Lighting, L.L.C.

700 \_\_\_\_ ENV \_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_