# Remote Transformer-2x300W EI 12v

#### DESCRIPTION

This remote electronic transformer converts standard 120 volt line-voltage to 12 volts, providing the necessary voltage for powering a Two-Circuit MonoRail low-voltage lighting system. Each transformer includes fast-acting short circuit and overload protection that will safely turn the system off should a short occur. Once the short has been removed the unit can be reset by simply flipping the wall switch off and back on. Transformer power lamps totaling up to 600 watts. Mounted on a plate with junction boxes.

# 228 mm 330 mm



#### INSTALLATION

This transformer must be installed in a remote but accessible location (such as above the ceiling or in a closet). To simplify installation the transformer should be located no more than 20' from the run or power feed. The electrician will need to supply the proper gauge conductor from the transformer to the power feed location based on distance (see Low-Voltage Wire Size Table, below).

#### OTHER

12 volt output transformers require the use of 12 volt lamps. Use with a single-feed Two-Circuit canopy or other power feed option (sold separately).

#### LOW-VOLTAGE WIRE SIZE TABLE

Use to determine the correct THHN wire size for a recommended 3 percent drop in voltage at the specified wattage. The length shown is the length of wire from the transformer to the power feed.

.,							
12 Volt	5 ft.	6-15 ft.	16-20 ft.	21-40 ft.	41-60 ft.	61-90 ft.	
300 Watt	#10 GA	#6 GA	#4 GA	#1 GA	1/0	3/0	

#### WEIGHT


2.52lb / 1.14kg ±



remote transformer-2x300w el 12v

### ORDERING INFORMATION

## 700AT2X300EL





7400 Linder Avenue Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

