



BRAND

Juno Lighting

DESCRIPTION

6 Inch 120 Volt 600 Lumen Generation 4 LED IC Remodel Housing is a dedicated LED, Air-Loc remodel housing with integral light engine. Shallow housing allows for fit in 2 x 6 construction. IC remodel housing for remodel application where back side of ceiling is not accessible and can be completely covered with insulation. When used with supplied ALG kit, stops infiltration and exfiltration of air, reducing heating and air cooling costs. Replaceable light engine mounts directly to housing and incorporates the latest generation high lumen output LED array. Comparable light output to 65 watt BR30 incandescent while consuming less than 11.5 watts. Available with 2700K, 3000K, 3500K, or 4100K color temperature, 90 minimum CRI. Wide flood distribution shipped as standard. Optional optic accessories available, sold separately. 120 volt only driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers (see attached manufacturer dimmer compatibility reference). Life rated for 50,000 hours at 70 percent lumen maintenance. Energy Star. Title 24 compliant with select trims. UL listed for damp locations. 14.5 inch length x 7.25 inch width x 5.1 inch height. A complete fixture includes a housing and trim, sold separately.





Shown in: Aluminum

TRIM COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	11.5W
DIMMER	Dimmable
DIMENSIONS	14.5"L x 7.25"W x 5.1"H
INTEGRATED LED MODULE	
LAMP	1 x LED/11.5W/120V LED

Technical Information

LAMP COLOR	2700K
COLOR RENDERING	90 CRI
LAMP LIFE	50000 hours
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel IC

SPEC # JUN111045



6 3/4" CEILING CUTOUT

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE