



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Surface Mount Wet Location Light Channel features 24 volt Soft Strip inside a slim, paintable aluminum extrusion. LCSMC includes 2.5 watts per foot commercial grade SS2C LED Soft Strip with (VW) 2700K or (WW) 3000K, 95CRI, or (AW) 2400K, (NW) 3500K, (CW) 4000K, or (DW) 5700K color temperature, 85CRI. 43 lumens per watt/126 lumens per foot. 50,000 hour lamp life. The 61 degree white diffuser lens projects a clean line of light and eliminates LED dots, while the clear lens provides maximum light levels. Available in various sizes up to 120 inches. Fixtures include LC-MCL mounting clips every 2 feet and can be linked end-to-end with plug-in or flexible connectors to a maximum of 40 feet away. System is powered by a dimmable electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Philips Sunrise SRI200ZTUNV. ETL listed for wet locations. Major components made and assembled in the USA. 5 year warranty. Required power supply, dimmer control and optional accessories sold separately. Product is built to order.



SHADE COLOR	White
BODY FINISH	White
WATTAGE	0.6W
DIMMER	Dimmable
DIMENSIONS	3"L x 0.8"W x 0.68"H
INTEGRATED LED MODULE	
LAMP	1 x LED/0.62W/24V LED

Technical Information

LUMINOUS FLUX	43 lumens
LUMENS/WATT	69.35
LAMP COLOR	2700K
COLOR RENDERING	95 CRI

SPEC # EDG122287



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE
