



BRAND

PureEdge Lighting

DESCRIPTION

Surface Mount Light Channel with 45 degree extrusion features 24V Soft Strip inside a slim, paintable aluminum extrusion. LC45 uses SS2P Soft Strip with 2.3 watts per foot and 3000K Warm White color temperature, 80+CRI LEDs. 37 lumens per watt/115 lumens per foot. 32,000 hour average lamp life. Finish available in Satin Aluminum or White. The white diffuser lens projects a clean line of light and eliminates LED dots, while the clear lens provides maximum light levels. Sold in a 12. 22 amd 63 inch length. Fixtures include LC-MCL mounting clips every 2 feet and CON-2W joining connectors. The 8 foot cables on each end can be hard wired together linking segments for a maximum of 40 feet. System is powered by an electronic low voltage or 0-10V remote power supply. ELV power supplies include a 60, 100, 2X100, 3X100 or 4X100 watt option, dimmable with Legrand Adorne ADTP703TU, Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600, or Lutron Radio Ra 2. 0-10V power supplies include a 96, 2X96, 3X96 or 4X96 watt option, dimmable with Philips Sunrise SR1200ZTUNV. ETL listed. Major components made and assembled in the USA. 5 year warranty. Required power supply, dimmer control and optional accessories sold separately. Product is built to order. Limited quantities available.




SHADE COLOR	Diffused Lens
BODY FINISH	Satin Aluminum
WATTAGE	1W
DIMMER	Dimmable
DIMENSIONS	3"L x 0.9"H x 0.9"D
INTEGRATED LED MODULE	
LAMP	LED/1W/24V LED

Technical Information

LUMINOUS FLUX	31 lumens
LUMENS/WATT	31.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI

SPEC # EDG122418



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE