



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Aurora Dual Square Edge housing and trim is a specification grade, adjustable accent fixture for plaster or drywall construction. Two 12 volt GU5.3 MR16 IR 37 watt maximum lamps or two MR16 LED 12 volt 7 watt, one per socket, not included. The flush mounted rigid plaster plate, which is finished into the ceiling, maintains a flat finish and defines the Truly Trimless Pure edge (knife edge) 3.3 inch aperture. Combined with the Aurora dome and the tilt gear hidden behind the lamp creates a clean internal lock. Dome features anodized soft haze finish and hides electrical hardware, tilting for easy access to junction box and transformer. Designed to accommodate ceiling thickness from .50 to 1.25 inches. Features hot aiming with Philips screwdriver offering 20 to 45 degree vertical adjustment and 362 degree horizontal rotation without beam clipping. Includes standard 120 volt magnetic transformer, IC and air-tight, suitable for remodel or new construction. Secondary output voltage is 11.8 volts. Includes two snoots and soft focus lenses, with room for two lamps and two additional accessories. ETL listed for damp locations. 14.75 inch length x 12.1 inch width x 5.75 inch height. Aurora Gear Cover and light control accessories sold separately.



TRIM COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	74W
DIMMER	Low Voltage Magnetic
DIMENSIONS	14.75"L x 12.1"W x 5.75"H
BULB NOT INCLUDED	
LAMP	2 x MR16/GU5.3 (bipin)/37W/12V Halogen 2 x MR16/GU5.3 (bipin)/12V LED



Technical Information

FUNCTION	Downlight
CEILING TYPE	Drywall Trimless/Flush
HOUSING TYPE	New construction IC Airtight
HOUSING HEIGHT	6"
APERTURE SHAPE	Square

SPEC # EDG155751



3.3 aperture
Truly Trimless



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE
