



BRAND

Eurofase

DESCRIPTION

NC04-B 4 Inch 12 Volt Non-IC New Construction Housing is designed for open ceilings (pre-drywall). Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. These housings incorporate a plate and hanger bars so the housing can be positioned in the desired location. New construction type housing consists of a frame in plate with the housing components built onto the plate. Includes magnetic transformer. One 50 watt, 12 volt MR16 type GU5.3 base bulb (or LED equivalent) is required, but not included. Dimmable with a low voltage magnetic dimmer, sold separately. A complete fixture requires a housing and trim, sold separately.




Shown in: Aluminum

TRIM COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	7W
DIMMER	Low Voltage Magnetic
DIMENSIONS	11.63"L x 11.63"W x 5.25"H
BULB NOT INCLUDED	
LAMP	1 x MR16/GU5.3 (bipin)/12V LED

Technical Information

CEILING TYPE	Drywall with Trim
HOUSING TYPE	New Construction NON IC
HOUSING HEIGHT	6"
APERTURE SIZE	4.000"

SPEC # EUF184749



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE