



BRAND



Hadco by Signify

DESCRIPTION

IL116 Inground Uplight housing is fabricated from a single piece of compression-molded fiberglass reinforced polyester composite, pressure tested to ensure water will not wick or leak through. Finish in Bronze or Natural Brass. Trim ring is a textured composite material. Clear, convex, tempered, soda-lime glass for high impact resistance. 2200 pound live-load rated, standard walk-over lens. One 75 watt 12 volt GU5.3 MR16 halogen lamp is required, but not included. Covered MR16 lamp is recommended to protect inner capsule lamp. Pre-wired with 3 foot pigtail of 18-2 AWG wire. Includes low voltage quick connector LVC3 for easy hook up to the low voltage supply cable not included. 6.6 inch diameter x 8.4 inches high. ETL listed for wet location. Required remote transformer and optional mounting and optical accessories sold separately.



| | |
|--------------------------|--|
| SHADE COLOR | Clear |
| BODY FINISH | Bronze |
| WATTAGE | 75W |
| DIMMER | Dimmable |
| DIMENSIONS | 6.6"W x 8.4"H |
| BULB NOT INCLUDED | |
| LAMP | 1 x MR16/GU5.3 (bipin)/75W/12V Halogen 1 x MR16/GU5.3 (bipin)/12V LED |



SPEC # HAD21643

| COMPANY | PROJECT | FIXTURE TYPE | APPROVED BY | DATE |
|---------|---------|--------------|-------------|------|
| | | | | |