

NW3000CM 3.5 Inch 37-50W MLV Non-IC Shallow New

 Construction



Description:

NW3000CM 3.5 Inch Low Voltage Non-IC Shallow New Construction Housing is designed for new construction applications and damp locations. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Below ceiling accessible. Takes up to 1.5 inch ceiling thickness. Low voltage 12 volt magnetic transformer is included. One 37-50 watt, 12 volt GU5.3 MR16 bulb is required, but not included. Wattage dependent on housing/trim combination. Dimmable with a low voltage magnetic dimmer. Consult bulb manufacturer for low voltage magnetic dimmer compatibility when using LED bulb option. Suitable for damp locations. UL listed. Ceiling cutout 3 5/8 inch. Housing dimensions: 15.38 inch length x 10 inch width x 3.4 inch height. A complete fixture includes a housing and trim, sold separately.

Shown in: Galvanized Steel

List Price: \$106.75
 Our Price: \$76.86

Shade Color: N/A
 Body Finish: Galvanized Steel
 Lamp: 1 x MR16/GU5.3 (bipin)/50W/12V Halogen
 1 x MR16/GU5.3 (bipin)/12V LED
 Wattage: 50W
 Dimmer: Low Voltage Magnetic
 Dimensions: 15.38"L x 3.4"H x 10"W

Technical Information

Ceiling Type: Drywall with Trim
 Housing Type: New Construction NON IC
 Housing Height: 4"
 Aperture Size: 3.500"
 Product Dimensions: cutout 3 3/4 inch

Product Number: CLT3814			
Company:		Fixture Type:	Date: Mar 17, 2018
Project:		Approved By:	

#0314RE-3000CM-004H1-OOMT

Phone: 866-954-4489 Fax: (773) 883-6131

Address: 1718 W. Fullerton Ave. Chicago IL 60614

www.Lightology.com