

IRI41444







BRAND Iris

DESCRIPTION

P3MR Platform, 3 inch IC Air-Tight new construction housing is a specification grade residential housing that accepts low voltage MR16 lamps. Air-Tight to prevent energy loss, room drafts, dust marks on ceiling, and reduce sound transmission. Designed for use in insulated ceilings with direct contact to insulation. Transformer included. A complete fixture requires a platform (housing) and 3 inch optical element (trim), sold separately. Compatible with following trims: E3MR, E3MRBB, E3DNPIN, E3LWW, E3SLOT, E3AA, E3AABB, E3AA20, E3PIN, E3PIN LARGE, E3PINRD, E3PIN OVAL, E3SA, E3AASR, E3AASRPIN, E3SR using max 50 watt lamps; UL listed. Damp location listed. IBEW union made. Lamp ratings based on trim selected, sold separately. 15.75 inch lenght x 10 inch width x 9 inch height.



TRIM COLOR N/A **BODY FINISH** Aluminum WATTAGE N/A DIMMER Low Voltage Magnetic DIMENSIONS 15.75"L x 10"W x 9"H **BULB NOT INCLUDED** LAMP 1 x MR16/GX5.3/12V Halogen Technical Information CEILING TYPE Drywall with Trim HOUSING TYPE New construction IC Airtight HOUSING HEIGHT PRODUCT DIMENSIONS Ceiling Cutout: 4.38 In

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE

IRI41444

SPEC #