



BRAND

Juno Lighting


DESCRIPTION

TL601E-25 12 Volt 10 Watt Electronic Surface Mount Driver/Transformer is rated for 0.5 to 25 watts incandescent or LED total load, 120VAC input. Made of 18 gauge die formed steel with powder coat finish available in White or Black. Supplied with die-cast fitting for 3/8 inch flexible metal conduit. 18 inch lead wires provided to connect output to trac feed connector. Driver should be mounted within 18 inches of track and maximum run length from driver input should not exceed 21 feet. Replaceable fuse on primary. Incandescent loads can be dimmed with high quality dimmers designed for use with electronic transformers. LED loads may be dimmed using only dimmers that have been tested and qualified by Juno for use with Juno LED fixtures including: Leviton Acenti ACE06-1L, Lutron Diva DVELV-300P, Lutron Nova T NTELV-300, Lutron Maestro MAELV-600, Lutron Skylark SELV-300P, Lutron Faedra FAELV-500, or Lutron Spacer SPSELV-600. UL listed. Suitable for damp locations. 5.5 inch length x 1.5 inch width x 1.1 inch height. For use with Juno Trac 12 miniature low voltage track system using LED or incandescent luminaires.



Shown in: White

SHADE COLOR	N/A
BODY FINISH	White
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	5.5"L x 1.5"W x 1.1"H
LAMP	N/A



SPEC # JUN48900

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE