



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Light Channel Mill Work LED features the Soft Strip Premium 2 (SS2P) 12 Volt inside a slim paintable aluminum extrusion. Fits in a minimum .75 inch thick board. Finish in Satin Aluminum. The 61 degree white diffuser projects a clean line of light and eliminates LED dots, while the clear lens provides maximum light levels. The linear system is sold in 2 inch increments up to 96 inches and includes 4 spring clips per foot. Fixtures can be linked end-to-end with plug-in flexible connectors for a maximum run of 25 feet. At only 2.3 watts, each foot of Light Channel contains 36 Warm White 3000K 80CRI LEDs with excellent color rendering, delivering 115 lumens per foot. 32,000 hour average lamp life. The fixtures are powered by a 60 watt PSB-60W-ELV-12VDC power supply, sold separately. Dimmable with an electronic low voltage dimmer (tested and approved include Lutron DIVA DVELV-300P, Lutron Skylark SELV-300P, or Lutron Maestro MAELV-600). Rated for indoor applications only. ETL listed. Includes 5 year warranty. Major components made and assembled in the USA. Required power supply, dimmer and optional mounting accessories, sold separately. Limited Quantities Available. Please call for more information. Product is built to order.



SHADE COLOR	Clear Lens
BODY FINISH	Satin Aluminum
WATTAGE	18.4W
DIMMER	Low Voltage Electronic
DIMENSIONS	96"L x 1.25"W x 0.7"H
INTEGRATED LED MODULE	
LAMP	1 x LED/12V LED

Technical Information

LUMINOUS FLUX	920 lumens
LUMENS/WATT	50.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI

SPEC #	EDG57224
---------------	----------



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE