



BRAND

PureEdge Lighting

DESCRIPTION

Soft Line Indirect LED Lighting System provides soft, ambient, indirect illumination for decorative and architectural applications. For compact shipment and storage, Soft Line coils like a retractable tape measure. When uncoiled, the Soft Line becomes a 1.25 inch wide cupped, rigid aluminum channel that can be mounted on any angle between opposing wall, ceiling or floor surfaces. Soft Line is field-cuttable. Soft Line features a double row of 24 volt Soft Strip in 2700K, 3000K, 3500K, 4000K or 5700K color temperature. Includes Soft Line channel, a pair of power feed and non-power feed turnbuckles and a double row of LED Soft Strip. Soft Line 24 inch standoff, sold separately. Turnbuckles support Soft Line on any angle from 0-60 degrees, feed power from one end and mount to a standard 4 inch square electrical box with round plaster ring. Turnbuckles may be reversed and mounted (opposite the power feed) to a ceiling, wall or floor. Lengths over 20 feet require power feed at both ends. System is powered by a remote Universal (UNI) or Lutron Hi-Lume power supply sold separately. ETL listed. Title 24 compliant when used with a Universal (UNI) power supply. Power supply, standoff, and dimmer sold separately.



SHADE COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	50W
DIMMER	Dimmable
DIMENSIONS	120"L x 1.25"W
INTEGRATED LED MODULE	
LAMP	1 x LED/50W/24V LED

Technical Information

LUMINOUS FLUX	5780 lumens
LUMENS/WATT	115.60
LAMP COLOR	3000K
COLOR RENDERING	95 CRI

SPEC # EDG69737

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE