


ASSEMBLY & INSTALLATION INSTRUCTIONS

B546

Prisma 3 Light Sconce 201357



HUBBARDTON FORGE.

Component Parts

- A Fixture**
- B Mounting Bracket**
- C Ground Screw**
- D Cupped Washer**
- E #8 Screws (4)**
- F Socket (3)**
- G Bulb (3 - Not Included)**
- H Glass (3)**
- I Thumb Screws (6)**
- J Threaded Tabs (6)**

Prisma 3 Light Sconce 201357

CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician. This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.*

Caution: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

Please Note: After installation extra hardware and accessories are possible; our kits are used on multiple products.

To Install Fixture (Figure 1)

CAUTION: BE SURE POWER IS OFF AT THE MAIN BREAKER BOX PRIOR TO INSTALLATION.


1. Carefully unpack the fixture (A) from the carton.
 2. Remove mounting bracket (B) from fixture (A).
 3. Thread the wires in the electrical box through the hole in the mounting bracket (B) while moving the bracket into position. Place mounting bracket over electrical box and secure with two machine screws (not provided).
- Note:** A new electric box comes with screws. When replacing a fixture, retain the existing screws for use.
4. Attach a pigtail lead to the mounting bracket (B) using the ground screw (C) and cupped washer (D) found in kit bag.
 5. Hold fixture (A) close to wall. Using suitable wire connectors (not provided), connect fixture wires to supply wires (white to white and black to black). Connect all ground wires (bare copper or green to bare copper or green).

CAUTION: MAKE SURE WIRE CONNECTORS ARE TWISTED ON SECURELY, AND NO BARE WIRE IS EXPOSED.

6. Place fixture (A) over mounting bracket (B). Secure with #8 screws (E) on top and bottom of fixture.

Note: Be sure no wires are pinched between fixture and wall.

7. Follow steps on following page to complete installation.




(Figure 1)



Prisma 3 Light Sconce 201357

To Install Glass (Figure 2)

1. Carefully unpack glass (H).
2. Thumb screws (I) are shipped installed in threaded tabs (J). Loosen thumb screws before installing glass. It is not necessary to completely remove screws.
3. Slide glass (H) into fixture (A). Center in slots.
4. Tighten thumb screws (I) evenly to secure glass (H).
5. Install bulb (G), not included, into socket (F).
6. Repeat for remaining glass and bulbs.
7. Restore electricity at main breaker.



(Figure 2)

If you need further assistance, or find that you are missing any parts, please contact the dealer from which you purchased this product. We hope you enjoy your fixture!

*** Hubbardton Forge will not be liable for injury or damage caused by improper installation, lamping or use of this fixture.**



HUBBARDTON FORGE.