## **LED Flush Mount**

## FM45316

## START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- · Wear gloves at all time during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

**Technical Support**: 1-855-855-8926

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) or TRIAC type of dimmer for dimming application
- 120V input

Remove fixture from its original package
Separate mounting plate (1c) from canopy (2a) by

removing canopy screws (2b)

 Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package

4. Secure mounting plate (1c) to mounting surface with anchors (1f) and screws (1g)

**5.** Make proper electrical connections (**black** to **hot** "L", **white** to **neutral** "N", **ground** to "**GND**") with wire nuts (**1b**) provided in hardware package and place driver (**4a**) inside canopy (**2a**)

**6.** Attach canopy **(2a)** to mounting plate **(1c)** with canopy screws **(2b)** 

5a.

3500K 4000K

3000K

**1.** Choose color temperature by using slider (5a)



