

ASSEMBLY INSTRUCTIONS


Formosa 5" Elongated Flush Mount Item # KW4903

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver



1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate (B) from fixture (E) by removing ball caps (D).
3. Connect driver (G) input neutral wire (white) to the supply neutral wire (usually white) using wire nut (A).
4. Connect driver (G) input hot wire (black) to the supply hot wire (usually black) using wire nut (A).
CAUTION: Do not reverse the hot and neutral connections.
5. Insert driver (G) into junction box.
6. Install mounting plate (B) to the junction box and secure with mounting screws (C).
7. Connect supply ground wire (usually green or bare copper) around the green grounding screw (see diagram 1). Tighten.
NOTE: It is imperative that the fixture is grounded.
8. Connect quick connector (F1 & F2) together.
9. Install fixture (E) to mounting plate (B) and secure with ball caps (D).
10. Remove protective caps (H) from light source base, then thread light source (I) to light source base (see diagram 2).
NOTE: Discard protective cap (H) after assembly.

ASSEMBLY INSTRUCTIONS

Formosa 5" Elongated Flush Mount Item # KW4903

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Thread shade (**J**) to light source base (see diagram 2).

NOTE: Do not overtighten otherwise shade could become damaged.

CARE INSTRUCTIONS: Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.

