


## ASSEMBLY INSTRUCTIONS

### ITEM DESCRIPTION:

ITEM NO.: DWC70	NAME: ITALO SCONCE
MATERIAL: METAL AND CRYSTAL	FINISH: ANTIQUE BRASS
SOCKET TYPE: : LED	SOCKET QTY: 2
BULB WATTAGE: 6W	
VOLTAGE: 110V-120V	ITEM NET WEIGHT: 8LBS



### PARTS INCLUDED:

Mounting Plate(A)	Qty: 1PC	Mounting Screw(J)	Qty:2PCS
Back Plate(B)	Qty: 1PC	Plastic Wire Cap(K)	Qty:3PCS
Canopy Screw(C)	Qty:2PCS	Crystal Post(F)	Qty:2PCS
Lamp Body(D)	Qty: 1PC	Metal Post(G)	Qty:2PCS
Allen Wrench(E)	Qty: 1PC		

### HARDWARE INCLUDED:

Mounting Screws	Qty: 2PCS
Canopy Screws	Qty: 2PCS
Green Ground Screw	Qty: 1PC
Plastic Wire Cap	Qty: 3PCS

### TOOLS NEEDED (Not Included):

1 Screwdriver
---------------

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.



### TO ASSEMBLE:

1. Shut off the main electrical supply from the main fuse box/circuit breaker.
2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
3. Gently pull wiring down from junction box and allow to hang.
4. Remove the mounting plate(A) from the back plate(B) by loosening the canopy screw (C )using an Allen wrench (E).
5. Place the mounting plate(A) over the center of the junction box.
6. Align the holes in the mounting plate (A) with the holes in the junction box and secure it with two mounting screws (J). Secure the screws using a Phillips head screwdriver.
7. Connect ground wire from wall to ground wire from lamp using wire caps (K).
8. Attach house wire to lamp wires as shown. Fasten the pairs together with a wire caps .
9. Gently tuck the wire caps (K) neatly into the junction box.
10. Attach front face of light to back plate by inserting canop screw (C) through predrilled holes in front face and into back plate as shown. Tighten screw using an Allen wrench (E).
11. Attach the crystal post (F) and the metal post (G) to lamp body (D) by turning clockwise until it is tight.
12. Restore power to junction box and test fixture.

### CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

For customer service questions call 1-800-338-2150

ARTERIO RS