



# ASSEMBLY INSTRUCTIONS FOR YOUR ELLIOTT FLUSH MOUNT

## IMPORTANT SAFETY INSTRUCTIONS:

- \* These instructions are provided for your safety.
  - \* It is very important that they are read completely before beginning the installation of your fixture.
  - \* **WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.**
  - \* If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. requirements.
- If there are any questions, contact a qualified electrical contractor.

## ASSEMBLY INSTRUCTIONS:

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/ CIRCUIT BREAKER.
2. Remove all parts from carton and discard packing materials. Place the parts on a level surface.
3. Remove finial (H), washer (I), and diffuser (J). Set three parts aside.
4. Remove mounting plate (A) from shade (D) by removing decorative nuts (C). Set shade (D) and decorative nuts (C) aside. Lift mounting plate (A) to the ceiling outlet box.
5. Attach mounting plate (A) to ceiling outlet box using screws (B).
6. Lift shade (D) to mounting plate (A). Pull wires from ceiling outlet box through the hole in mounting plate (A).
7. Make the proper electrical connections noted in steps 8 through 10. A LICENSED ELECTRICIAN IS RECOMMENDED.
8. Attach ground wire from fixture (green or copper in color) to ground wire from outlet box. Fasten wires together with wire nut (F) and tightly wrap connection with electrical tape.
9. Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (F) and tightly wrap connection with electrical tape.
10. Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (F) and tightly wrap connection with electrical tape. Gently push wire connections back into the ceiling outlet box.
11. Align holes in the shade (D) to the two screws on the mounting plate (A). Thread both decorative nuts (C) onto the two screws to lock shade (D) to mounting plate (A).
12. Install three 5W G9 Bi-Pin LED bulbs (K) into three sockets (E).
13. Lift diffuser (J) to threaded piece (L), followed by washer (I). Thread the finial (H) onto the threaded piece (L) to lock diffuser (J) and washer (I) to the shade (D).
14. Reconnect main electrical supply at the fuse box/ circuit breaker and test the fixture.

