



ASSEMBLY INSTRUCTIONS FOR YOUR BAMBOO 42-LIGHT CHANDELIER

IMPORTANT SAFETY INSTRUCTIONS:

- *These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.
- *Turn off power at switch before replacing bulbs, making sure fixture has had sufficient time to cool down.
- *If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. requirements. If there are any questions, contact a qualified electrical contractor.
- *WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.
- *This fixture is UL rated for dry locations.

ASSEMBLY INSTRUCTIONS:

- 1.SHUT OFF ELECTRICAL SUPPLY AT CIRCUIT BREAKER.
- 2.Remove all parts carefully from the carton. Do not throw away any parts.
- 3.Remove mounting plate (A) from canopy (D) by removing canopy screws (E). Set canopy screws (E) aside.
- 4.Affix mounting plate (A) to ceiling outlet box with mounting plate screws (B) provided. If desired, use appropriate hardware in support slots (F) to add additional support.
- 5.Measure desired drop for fixture to hang and add/remove extension tubes (J) as needed. Guide wiring through extension tubes before threading tubes together. ****TO ADD/REMOVE EXTENSIONS: (Un)Thread the threaded nipple of one extension into/out of the threaded opening of the next extension. Make sure electrical cord is pulled tight when threading extensions together to prevent damage to the wiring.****
- 6.Thread the bottom extension tube (J) onto threaded tube (K).
- 7.Guide wiring from top extension (J) through loop (I), quick link (H) and hang straight (G), exiting canopy (D). Lift canopy (D) to ceiling outlet box.
- 8.Make proper electrical connections described in steps 9-11.
A LICENSED ELECTRICIAN IS RECOMMENDED.
- 9.Attach ground wire from fixture (green or silver in color) to ground wire from outlet box. Fasten wires together with wire nut (C) and tightly wrap connection with electrical tape.
- 10.Attach hot wire from fixture (black in color or smooth side of wire) to hot wire from outlet box. Fasten wires together with wire nut (C) and tightly wrap connection with electrical tape.
- 11.Attach neutral wire from fixture (white in color or ribbed side of wire) to neutral wire from outlet box. Fasten wires together with wire nut (C) and tightly wrap connection with electrical tape.
- 12.Carefully push wire connections back into ceiling outlet box.
- 13.Place canopy (D) over mounting plate (A). Thread canopy screws (E) into holes in canopy (D), and mounting plate (A) to secure fixture to ceiling.
- 14.Install forty two 25W MAX. G16.5, Candelabra base bulbs into sockets.
- 15.Reconnect main electrical supply from the fuse box/circuit breaker and test the fixture.

