

STYLE NO.: 21577 PARTS LIST& HARDWARE LIST:

| 1 | Canopy | 1pc | 7 | Wire Connector | 3pcs |
|---|--------------------------|------|----|----------------|-------|
| 2 | Universal Bar | 1pc | 8 | Plastic Washer | 2pcs |
| 3 | Finial | 2pcs | 9 | Hasp | 5pcs |
| 4 | Outlet Box Screw(1-1/8") | 2pcs | 10 | Nut | 2pcs |
| 5 | Green Ground Screw | 1pc | 11 | Pin | 15pcs |
| 6 | Mounting Screw(2-3/4") | 2pcs | 12 | Glass Shade | 5pcs |

^{*}Please make sure you have all the parts indicated above before you begin assembling this item.We suggest a professional electrician for all lighting fixture installations. Please read wiring instructions before you begin assembling and installing your Ceiling Lamp

WARNING: <u>Before installing</u>, make sure electricity supply is shut off to avoid a possible electric shock.

ASSEMBLY INSTRUCTIONS

- 1.Take the parts carefully out of the carton, Place them on a flat surface, and make sure the parts will not be damaged.
- 2.Remove the Ball finial under the Canopy from the Mounting Screws, and take out the Universal Bar. Attach the Universal Bar to the Outlet Box by using two Outlet Box Screws. (See Figure 1)
- 3.Adjust wire length as needed for installation, remove excess.
- 4.Install the Ground Wire in the Universal Bar with the supplied Green Ground Screw.
- 5.Place the null wire ,white wire evenly against the null wire from the Outlet Box and place the live wire,black wire evenly against the live wire from the Outlet Box. (Connecting the Wire--- See Figure 2)
- 6.After the wires are connected.Pull the black fabric wire to adjust the length,Tighten it by the hasp. tuck them carefully inside the Outlet Box.(See Figure 3)
- 7.Attach the Canopy to the Mounting Screws and secure with two Ball Finials(See Figure 1) 8.Install 5*60W,E12 bulbs(not Included) into the socket of the fixture.
- 9. Secure Glass shade with pin on round metal sheet.

UTTFRMOST

ASSEMBLY INSTRUCTIONS



