

UTTERMOST

ASSEMBLY INSTRUCTIONS

STYLE NO.: 21638 PARTS LIST& HARDWARE LIST:

1	Canopy	1pc	9	Chain#2	3pcs
2	Universal Bar	1pc	10	Thread Pipe#1	1pc
3	Outlet Box Screw(1-1/8")	2pcs	11	Thread Pipe#2	1pc
4	Green Ground Screw	1pc	12	Plastic Washer	2pcs
5	Mounting Screw(2-3/4")	2pcs	13	Glass Diffuser	1pc
6	Wire Connector	3pcs	14	Nut	1pc
7	Quick Link	2pcs	15	Finial	1pc
8	5 Feet Chain#1	1pc			

*Please make sure you have all the parts indicated above before you begin assembling this item. We suggest a professional electrician for all lighting fixture installations. Please read wiring instructions before you begin assembling and installing your Ceiling Lamp

WARNING: Before installing, make sure electricity supply is shut off to avoid a possible electric shock.

ASSEMBLY INSTRUCTIONS

1. Take the parts carefully out of the carton, Place them on a flat surface, and make sure the parts will not be damaged.
2. Fasten the Cross bar to the outlet box . Secure the Nipple onto the Canopy with Loop .
3. Adjust chain and wire length as needed, remove excess. Thread Quick Link into Loop on the Canopy, then Quick Link into Ring on the top of Pendant body. Hand tighten until snug.
4. The Thread Pipe#2 pass through the Plastic Washer and Glass Diffuse, locked with the Nut, and then secure the Finial on the end of Thread Pipe#2 .
5. Lift upward the Shade, rotate the Thread Pipe#1 into the Center Pipe. And then the Quick Ring to connect the ends of the Chain#2.
6. Pull the wire from the Canopy and then the center hole in the Cross Bar. The power supply wire consists of three wires, one black wire, one white wire and one green ground wire.
7. Connect the wires as shown :

A. Connect the House Ground Wire to the Fixture Ground Wire.

UTTERMOST

ASSEMBLY INSTRUCTIONS

B.Connect the House White Wire to the Fixture Supply Wire (White).

C.Connect the House Black Wire to the Fixture Supply Wire (Black).

D.Wrap each connected wire with Wire Nut and carefully stuff all of the connected wires into the Outlet Box.

8.Install 4*60W,E26 bulbs(Not Included) into the socket of the fixture.

