

## SPECIFICATION

TYPE:	Constant Current
DRIVER CURRENT (mA):	350
DRIVER VOLTAGE (V):	-
DIMMABLE:	Leading/Trailing Edge & 0-10V
ELECTRICAL CLASS:	Class 2
SUPPLY VOLTAGE (V):	108-305 AC
SUPPLY FREQUENCY (Hz):	47/63
POWER FACTOR:	0.9
MIN. OUTPUT VOLTAGE (V DC):	24.0
MAX. OUTPUT VOLTAGE (V DC):	42.0
MIN. OUTPUT POWER (W):	8.4
MAX. OUTPUT POWER(W):	14.7
INRUSH CURRENT(A):	6A Half Value Time 200µs @120V
IP RATING:	Damp
WORKING TEMPERATURE (°C):	-30 - +70
CONNECTION TYPE:	Trailing Wires
LENGTH (mm):	84.0
WIDTH (mm):	40.0
HEIGHT (mm):	25.0
MIN. CIRCULAR APERTURE (mm/inch):	48/1-7/8
MAX. LED DISTANCE (m):	To Be Advised
MANUFACTURER:	Efore
MODEL NUMBER:	RCL015-0350A
CERTIFICATION:	cURus



CODE: 6008061

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.