

SPECIFICATION

TYPE:	Constant Current
DRIVER CURRENT (mA):	700
DRIVER VOLTAGE (V):	-
DIMMABLE:	0-10V
ELECTRICAL CLASS:	Class 2
SUPPLY VOLTAGE (V):	108-305 AC
SUPPLY FREQUENCY (Hz):	47-63
POWER FACTOR:	0.9
MIN. OUTPUT VOLTAGE (V DC):	6.0
MAX. OUTPUT VOLTAGE (V DC):	16.0
MIN. OUTPUT POWER (W):	4.2
MAX. OUTPUT POWER(W):	11.2
INRUSH CURRENT(A):	<10.0 Amps @ 120Vac, cold start 25°
IP RATING:	Wet
WORKING TEMPERATURE (°C):	-30 - +60
CONNECTION TYPE:	Flying Leads
LENGTH (mm):	102.7
WIDTH (mm):	37.7
HEIGHT (mm):	24.0
MIN. CIRCULAR APERTURE (mm/inch):	43/1-11/16
MAX. LED DISTANCE (m):	To Be Advised
MANUFACTURER:	EPTronics
MODEL NUMBER:	LD12W-16-C0700-RD
CERTIFICATION:	cURus



CODE: 6008064

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.