

SPECIFICATION

TYPE:	Constant Current
DRIVER CURRENT (mA):	350
DRIVER VOLTAGE (V):	-
DIMMABLE:	Phase
ELECTRICAL CLASS:	Class 2
SUPPLY VOLTAGE (V):	120 AC
SUPPLY FREQUENCY (Hz):	50/60
POWER FACTOR:	0.9
MIN. OUTPUT VOLTAGE (V DC):	15
MAX. OUTPUT VOLTAGE (V DC):	46
MIN. OUTPUT POWER (W):	5.25
MAX. OUTPUT POWER(W):	16
INRUSH CURRENT(A):	<7A Max @120VAC, cold start
IP RATING:	WET
WORKING TEMPERATURE (°C):	-40 - +90
CONNECTION TYPE:	Trailing Wires
LENGTH (mm):	121.9
WIDTH (mm):	37.7
HEIGHT (mm):	24
MIN. CIRCULAR APERTURE (mm/inch):	43/1-11/16
MAX. LED DISTANCE (m):	-
MANUFACTURER:	Hatch
MODEL NUMBER:	LC16-0350P-120-D
CERTIFICATION:	cURus



CODE: 6008099

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.