## **Baton Reader LED**

# astro

#### General

Location:
Class:
Location Rating:
Driver Required:
Installation Orientation:
Fitting Method:
Main Material:
Dimensions (mm):
Dimensions (inch):
Cut Out Hole (mm/inch):

Recess Depth (mm/inch):

Cable Length (mm/inch): Gross Weight (lb): Interior cULus (Class I) Dry Mains 120V Wall Mount - Horizontal or Vertical 4" Octagon Box with included Canopy Kit Metal - Aluminium H: 508 W: 90.5 D: 112.5 H: 20 W: 3.56 D: 4.43 ---4.28

Yes - if installed in compliance with ADA 307.2, 308, 309.3, 309.4



CODE: 1475027 FINISH: MATT BLACK

9

CODE: 1475028 FINISH: MATT NICKEL

Ic Rating:

Ada Compliant:

Fire Rating:

### Lamp

Light Source:	Mid-Power LED
Wattage:	4.8W
Lamp Included:	Yes (Integral)
Maximum Lamp Length (mm/inch):	-
Luminous Flux (Im):	181
Colour Temp (K):	2700
Cri (Ra):	90
Macadam Ellipse:	3-Step
Tilt Adjustable Angle (°):	-
Rotation Adjustable Angle (°):	-
Average Lifetime (hrs):	54000
Beam Angle (°):	160.3

#### Electrical

Switched:	Yes
Dimmable:	No
Dimming Method:	-
Supply Frequency (Hz):	50-60
Driver/Ballast Voltage (V):	100-277
Driver Average Lifetime (hrs):	100000
Efficacy (Im/W):	38

## Additional Information:

Shade Included: Shade / Diffuser Material:	-	To maintain this product to its best condition, please view our care and cleaning guidelines on the support section of the astro website.
Shade/Diffuser Finish:	-	Astro® is a registered trademark of astro lighting limited. Astro lighting's
F Mark:	-	fixture designs and imagery are protected under U.S. And international intellectual property laws, and all rights to such designs and imagery are expressly reserved.

# **Product Elevations**

astro

Please note that some dimensions may vary slightly due to manufacturing tolerances, this includes cable entry and fixing holes.





