





LINEAR PATH LIGHT WITH ON BOARD DIMMING

6401

WAC

LANDSCAPE LIGHTING



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

WAC's Linear Path Light is a versatile and powerful LED solution for accenting or grazing: walls, paths and your landscape. An adjustable Anti-Glare Shroud lets you shield your light to avoid harsh visual glare and for more beam control. On-board brightness control feature will allow you to adjust your lumen output as desired for specific applications.

FEATURES

- On-board brightness control
- Low profile and discreet
- 180° fully rotatable fixture aiming
- Wide Flood Beam 110° x 80°
- Adjustable anti-glare shroud
- Good for soft ground, wood floor, and concrete
- Base mount, riser mount & extension mount
- Path & Accent applications
- 10' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed
- MLV dimmable with remote MLV dimmers

SPECIFICATIONS

- Input:** 9 - 15VAC (Transformer is required)
- Power:** 1 - 6W / 1.3 - 8.6VA
- Brightness:** 65 lm - 190 lm
- Beam Angle:** 110° to 80°
- CRI:** 85
- Rated Life:** 60,000 hours



On-Board Dimming Knob

ORDERING NUMBER

	Color Temp	Finish
6401	27 2700K	BK Black on Aluminum
	30 3000K	BZ Bronze on Aluminum
		BBR Bronze on Brass

6401-_____

Example: 6401-30BZ

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

LINEAR PATH LIGHT WITH ON BOARD DIMMING

6401

WAC

LANDSCAPE LIGHTING

Accessories

Additional Stake		9000-ST9-BZ	Bronze	Durable PVC stake	
Extension Rods		5000-X04-BZ, BK, BBR	4 in	Bronze	Extends distance between Accent light and Surface Mount Canopy, Stake, or Tree Mount box
		5000-X08-BZ, BK, BBR	8 in		
		5000-X12-BZ, BK, BBR	12 in		
		5000-X18-BZ, BK, BBR	18 in		
		5000-X24-BZ, BK, BBR	24 in		

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS
75W Max

9150-TRN-SS
150W Max

9300-TRN-SS
300W Max

9600-TRN-SS
600W Max



waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760