



CIRCUS upright POWER 0_1-10V 110V

ver. 20200404_Rev_0

year: 2015
code: 1732502A20150
type: surface lamp
application: indoor



Technical drawing
Size ref. image mm - inch



Technical data

Light source	LED
Circuit structure	LED module G2
Light emission direction	indirect
Power	49 W
Source lumens	7590 lm
Source efficacy	155 lm/W
Consumption	58 W
Delivered lumens	7380 lm
Luminaire efficacy	127 lm/W
Secondary	1400mA
Colour temperature	3000 K / variants page 2
Colour rendering index	90 CRI
Standard Deviation of Colour Matching	3 SDCM
Energy class	A
Safety class	I
Degree of protection	IP 20
Direct mounting on normally flammable surfaces	●
Operating temperature	+10° / +40°
CE	●
UL	○
Optional	
Emergency mode	○
Motion sensor	○
Directional	○

Packing

Net weight	
Packaging 1	
Packaging 2	
Packaging 3	
Packaging 4	
Packaging 5	

Structure

Material	aluminium
Finish	white / variants page 2


Diffuser

Material	pmma
Finish	satın / variants page 2

Electronics / Driver

Included	Yes
Quantity	1
Voltage	100-277V 50/60 Hz

Dimmable



Hanging cables

Stainless steel cables standard length (custom available)	○
Electric cable standard length (custom available)	-

Warranty

Duration	2 years
----------	---------

CIRCUS upright POWER 0_1-10V 110V

ver. 20200404_Rev_0

year: **2015**
code: **1732502A20150**
type: **surface lamp**
application: **indoor**

Available variants

Colour temperature

3000 k



4000 k



custom



Colour rendering index

CRI 80



CRI 90



CRI 95



custom



Structure finish

matt white



matt black



embossed white



embossed black



custom



Diffuser / Optical

opal



transparent



transparent
prismatic



satin



custom

