

**CAUTION - RISK OF FIRE** 

Installation of this fixture should be done by a

operation of this fixture.

licensed electrician or by a person familiar with local electrical codes and the construction and

### Assembly and **Installation Instructions** for Model's

## 30040FM

Warning please make sure the electrical breaker is shut off

before commencing with this installation

# Junction Box [Supplied by Others] A. Mounting Bracket B. Mounting Bracket Screws Electrical Connectors D. Fixture Assembly E. Knurled Knobs F. Acrylic Diffuser G. Metal Ring

Package Contents		
Part	Description	
Α	Mounting bracket	1
В	Mounting bracket screws	2
С	Electrical connectors	3
D	Fixture assembly	1
Е	Knurled knobs	2
F	Acrylic diffuser	1
G	Metal ring	1
Н	Metal finial	1

### Installing the fixture

please ensure the electrical breaker is in the Off position before commencing

- Attach the Mounting bracket (A) to the Junction Box [Supplied by Others] using the Mounting bracket screws (B).
- Connect the supply wires to the fixture wires using the supplied electrical wire connectors (C). White supply wire to the White fixture wire, Black supply wire to Black fixture wire and the ground Bare Copper or Green wire to the Green fixture wire. Once the electrical wire connectors are securely fastened it is recommended to tape these connectors with electrical tape.
- Attach the Fixture assembly (D) to the Mounting bracket (A) using the Knurled knobs (E).
- Secure the Acrylic diffuser (F) and Metal ring (G) to the Fixture assembly (D) using the Metal finial (H) and Threaded rod attached to the Fixture assembly.
- Switch on the electrical breaker switch and your new fixture is ready for many years of trouble free use.



H. Metal Finial