

CUBE ARCHITECTURAL DC-PD06

WAC LIGHTING

LED Pendant Mounts



24"
Extension rod for
additional length up
to 96"
DS-PDX24

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and 2 field cuttable 24" rods
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5%
 0-10V: 100% - 1%
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, UL & cUL wet location listed
 Energy Star® 2.2 rated Title 24 JA8-2016 Compliant
Operating Temp: -13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumen	CBCP	Reference Output ¹ Efficacy (Lm/W)	Light Distribution	Finish	
	DC-PD06	S Spot	16°	927	2700K	90	2820	18842	81		BK Black WT White BZ Bronze GH Graphite
				827	2700K	85	3385	22608	97		
				930	3000K	90	2925	19543	84		
				830	3000K	85	3535	23632	101		
				835	3500K	85	3630	24255	104		
				840	4000K	85	3665	24490	105		
	DC-PD0622	N Narrow	28°	927	2700K	90	2800	7992	80		
				827	2700K	85	3360	9589	96		
				930	3000K	90	2900	8290	83		
				830	3000K	85	3510	10024	100		
				835	3500K	85	3600	10288	103		
				840	4000K	85	3635	10388	104		
	DC-PD0622	F Flood	38°	927	2700K	90	2825	5451	81		
				827	2700K	85	3390	6540	97		
				930	3000K	90	2930	5654	84		
830				3000K	85	3545	6836	101			
835				3500K	85	3640	7017	104			
840				4000K	85	3675	7085	105			

DC-PD06- _____ - _____ ¹Reference output shows 35W output. Multiply by 0.7 to determine output for 22W combinations.

Example: **DC-PD06-S930-GH**




waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

MOUNTING ACCESSORIES

 <p>Extension Rod</p>	DS-PDX24	<i>One 24" extension rod for DC-PDSK Can be field cut</i>	Finish												
			<table><tr><td>BK</td><td>Black</td><td></td></tr><tr><td>WT</td><td>White</td><td></td></tr><tr><td>BZ</td><td>Bronze</td><td></td></tr><tr><td>GH</td><td>Graphite</td><td></td></tr></table>	BK	Black		WT	White		BZ	Bronze		GH	Graphite	
BK	Black														
WT	White														
BZ	Bronze														
GH	Graphite														

Example: **DS-PDX24-WT**