

WAC LIGHTING

Dimmable Remote Power Supply

60W/96W, 120-277VAC/24VDC

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Product

EN-24DC060-UNV-RB2 Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 60 Watt
 EN-24DC096-UNV-RB2 Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 96 Watt

L x W x H

8.81IN x 2.06IN x 1.25IN
 8.81IN x 2.06IN x 1.25IN

Example: **EN-24DC060-UNV-RB2**

DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supplies are intrinsically safer power supplies because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplies do not require conduit sheathed cable or clamp wiring techniques. This power supply has a low minimum load requirement of either 3W, 6W, or 9.6W to allow the use of LED products. May be dimmed using a TRIAC or electronic low voltage dimmer.


FEATURES

SPECIFICATIONS

Input:	100-277 VAC, 50/60Hz
Dimming:	ELV: %
Operating Temp:	-4°F to 104°F (-20°C to 60°C)
Standards:	UL, cUL, Damp Location Listed



LINE DRAWING:



WAC LIGHTING