

AMIGO 26W DOWNLIGHT

35141



LAMPING

- 1 x 26W Integrated LED TRIAC Dimming. For 0-10V and alternate dimming options consult Eurofase.
- **Beam angle:** 40°
- **Kelvin:** 3000K/3500K
- **Lumen per head:** 2560lm
- **CRI:** 90+

ELECTRICAL

- Class 2 dimmable constant current driver (included)
- Driver box mates to fixture by 12" flexible BX cable
- Thermally protected
- **Input voltage:** 120V
For 277V and 347V input options consult Eurofase

HOUSING

- 18 gauge powder coated steel housing
- Remodel housing complete with adjustable mounting clips suitable for 1/2" and 5/8" drywall
- New construction plate, insulated ceiling box and airtight IC box sold separately (refer to housing options)*

DIMENSIONS

- **Cut hole:** $\phi 6 \frac{1}{4}$ "
- **Fixture:** $\phi 6 \frac{3}{4}$ " x 5 1/4"H

PHOTOMETRICS

- See pg 44

CUSTOMIZATION

- For customization, please consult Eurofase

SPECIFICATIONS

LED	WATTS	LUMENS	KELVIN	DIMMABLE	CRI	BEAM ANGLE
	26W	2560lm	3000K / 3500K	TRIAC	90+	40°



FINISHES




-01 Black




-02 White

PRODUCT DIMENSIONS



$\phi 6 \frac{3}{4}$ "



$\phi 6 \frac{1}{4}$ "

ORDERING GUIDE

MODEL	KELVIN	FINISH
35141	-30 3000K	-01 Black
	-35 3500K	-02 White

EXAMPLE: 35141-30-01

***HOUSING OPTIONS (SOLD SEPARATELY):**


Refer to page 123 for housing specification

36205-011 NEW CONSTRUCTION PLATE



Dimension 12 3/4"L x 12 3/4"W x 1 3/8"H
Cut Hole $\phi 6 \frac{1}{4}$ "

36206-018 AIRTIGHT IC BOX



Dimension 12 3/4"L x 12 3/4"W x 1 1/2"H
Cut Hole $\phi 6 \frac{1}{4}$ "