



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant OmegaMirror™ glass
- Forward-facing task lighting
- Integrated defogger
- Suitable for wet environments, including showers
- Environmentally sustainable
- Energy efficient
- Fast lead times
- ADA compliant
- 3-year limited warranty
- Made in America with U.S. and global components

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- 604 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 124,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- Defogger serves as safety backing
- Low voltage (12V)

PRODUCT DESCRIPTION

To create our popular Acclaim™, we merged contemporary design, natural-looking LED lighting, and a highly versatile built-in defogger — offering great lighting to make shaving easier than ever and revolutionizing how your guests experience the shower.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting and corrosion-resistant glass, suitable for wet locations including showers. Mirror shall have built in defogger to keep glass clear and uniform light output in frosted areas, using-replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S. and global components and have a 3-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; transformer must be installed in a dry location, not behind mirror and at least 4 feet from wet environment, but within 25' of mirror
- Driver enclosure box requires recess for mounting
- Controlled by no-dimming on/off wall switch; light and defogger operate together
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements **
ISF-11.75x11.75-DF	11.75"W x 11.75"H x 2.85"D (298mm x 298mm x 72mm)	120/240 VAC, 14W
ISF-11.75x23.75-DF	11.75"W x 23.75"H x 2.85"D (298mm x 603mm x 72mm)	120/240 VAC, 32W
ISF-12.00x28.00-DF-DL***	12"W x 28"H x 4.22"D (305mm x 711mm x 107mm)	120/240 VAC, 33W

*Base model number shown only. To specify additional options, contact sales@electricmirror.com.

**Defogger specification: 24V. Power requirements included in overall lighted mirror power requirements listed above.

***12"x28" model comes standard with downlight

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

