

## ASSEMBLY & INSTALLATION

### INSTRUCTIONS FOR #617-1W &#617-2W

*Please read carefully and save these instructions, as you may need them at a later date.*

#### CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

#### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

#### ASSEMBLY AND INSTALLATION

1. At the center of the **FIXTURE MOUNTING PLATE (2)** there are eight perforated slots. Knock out the set matches your **ELECTRICAL OUTLET BOX (1)**.
2. Carefully pass the power supply (6&8) wires and the **SUPPLY GROUND WIRE (5)** through the center hole of the **FIXTURE MOUNTING PLATE (2)**. Secure the **FIXTURE MOUNTING PLATE (2)** to the **ELECTRICAL OUTLET BOX (1)** with **MOUNTING PLATE SCREWS (3)**. And make sure the **FIXTURE MOUNTING PLATE- HOLES FOR SCREWS (12)** are horizontal.
3. Attach the **BLACK SUPPLY WIRE (8)** to the **BLACK FIXTURE LEAD WIRE (9)** by using the **WIRE CONNECTOR NUTS (10)**. At the same manner, attach the **WHITE SUPPLY WIRE (6)** to the **WHITE FIXTURE LEAD WIRE (7)**. Loop the **FIXTURE GROUND WIRE (4)** around the **GROUND SCREW (11)** of the **BACK PLATE (2)**. (Note: Be sure to provide an extra 3" length of the **FIXTURE GROUND WIRE (4)** for connection to the **SUPPLY GROUND WIRE (5)**.) Tighten the **GROUND SCREW (11)**. Connect the remaining **FIXTURE GROUND WIRE (4)** to the **SUPPLY GROUND WIRE (5)** using a **WIRE CONNECTOR NUTS (10)**. Place wiring and connections inside the **OUTLET BOX (1)**.

#### ASSEMBLY AND INSTALLATION (Continued)

4. Place the **FIXTURE BACKPLATE (14)** onto the **FIXTURE MOUNTING PLATE (2)**, and secure thg **BACKPLATE MOUNTING SCREWS(13)** into the **FIXTURE MOUNTING PLATE- HOLES FOR SCREWS(12)**.
5. Screw light bulb into the socket and make sure it does not exceed the maximum wattage specified on the fixture's wattage rating label.
6. Thread the **GLASS SHADE(17)** into the **FIXTURE BODY(16)**till tight.

INSTALLATION IS NOW COMPLETED

