



SAFETY INFORMATION

Released Date: 2023-08-18

Please read and understand this entire manual before attempting to assemble, install or operate the product.


WARNING

- RISK OF ELECTRIC SHOCK - Before beginning installation, turn off electricity at the circuit breaker box or the main fuse box.
- RISK OF FIRE - Use bulbs specified by the markings and/or labels on the fixture.

CAUTION

- For your safety, read instructions completely before beginning installation.
- If in doubt about electrical installation, consult a licensed electrician.
- Turn off electricity to fixture before replacing the bulb(s).

TOOLS REQUIRED




CARE AND MAINTENANCE


- Wipe clean using soft, dry cloth or static duster. Always avoid using harsh chemicals and abrasives to clean fixture as they may damage the finish.

If you need further assistance call Quoizel Customer Care at 1-800-645-3184 (9:00am - 5:00pm EST), or visit us on-line at www.quoizel.com.

PACKAGE CONTENTS



MOUNTING HARDWARE



INSTALLATION

OPTION 1: PENDANT QP6224BWS


1

Install Rods

Optional Rods:


8 Feet Ceiling:
(2) 12"L Rods.

9 Feet Ceiling:
(2) 6"L Rods + (2) 12"L Rods.




2

Tighten hex nut inside of the ceiling canopy




3

Install Ceiling Canopy to Upper Rod



4


Install Crossbar Assembly



Outlet Box

5

Wiring



White wire from supply

White from fixture

Black (or red) wire from supply

Black from fixture


Ground wire from supply

Ground wire from fixture

Green ground screw

6

Install Ceiling Canopy to Crossbar Assembly



90Degree Swivel


For angled ceilings,
Swivel opening towards wall.

7


Install Bulb

Install the correct bulb referring to fixture markings and/or labels for maximum wattage.


Recommended Bulb Type (not included):



BULB BASE TYPE
Medium (E26)



BULB TYPE
TYPE A



INSTALLATION

OPTION 2: SEMI-FLUSH QSF6224BWS

* Set aside the (2) 6"L Rods and (2) 12"L Rods since they are not required for the semi-flush installation.



1

Remove Swivel

2

Install Ceiling Canopy

3

Install Crossbar Assembly

4

Wiring

5

Install Fixture to Crossbar Assembly

6

Install Bulb

Install the bulb referring to fixture markings and/or labels for maximum wattage.

BULB BASE TYPE
Medium (E26)

BULB TYPE
TYPE A

100W MAX

Your installation is now complete! Restore electricity and save this sheet for future reference.