

Lock LED Multi Linear Pendant LCKP Series

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	



Features

Perimeter illumination. Includes 9 ft. adjustable cord. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 Hz. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 60W = 3825 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification


All fixtures are cETLus listed for indoor damp locations.

Warranty


Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5-year from date-of-purchase.

Specifications and dimensions subject to change without notice.









Ordering Information:

		k						
Black	Satin Brass	Satin Nickel	LED	Lumens	CCT	L	W	Н
I CKDOQI ZODIRKI NIDZ	I CKDOOL ZODISBL NIDZ	I CKDOOL ZODIENII NIDZ	601//	7825	3000K	76"	Q"	Q"