Fixture Type: Catalog Number:

Catalog Null

Project: Location:

Paloma LED512

9.5W W Track Luminaire

System Type & Voltage	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish	
WHK 277 VAC	LED512	F 36°	27 2700K - 85	850	2105	BK Black	
WTK 120 VAC			30 3000K - 85	885	2195	PT Platinum	
			35 3500K - 85	910	2259	WT White	
			40 4000K - 85	920	2282		
			927 2700K - 90	710	1755		
			930 3000K - 90	735	1821		
		N 24°	27 2700K - 85	685	3152		
			30 3000K - 85	860	3286		
			35 3500K - 85	885	3382		
			40 4000K - 85	895	3417		
			927 2700K - 90	685	2628		
			930 3000K - 90	715	2727		
		S 19°	27 2700K - 85	800	3773		
			30 3000K - 85	835	3832		
			35 3500K - 85	860	4048		
			40 4000K - 85	870	4089		
			927 2700K - 90	670	3145		
			930 3000K - 90	695	3264		
			330 300011 30	055	520.		

Example: WHK-LED512F-27-BK

FEATURES

- High Output COB LED
- · Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Integral selector to choose between independently controllable track circuits
- Recessed driver hidden within W track
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum with regressed driver and cap ring.

Clear glass lens included.

Power: 9.5W

Input: 120 VAC, 50/60Hz

Dimming: ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED

3 Step Mac Adam Ellipse

Rated Life: 50000 Hours

Finish: Electrostatically Powder Coated: Platinum, White, Black

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Dry Location Listed, Title 24 JA8 Compliant



FINISHES:



LINE DRAWING:



Fixture Type:	
Catalog Number:	
Project:	
Location:	

Paloma LED512 9.5W W Track Luminaire

ACCESSORIES

	Model	Description	Finish
• • • • • • • • • • • • • • • • • • • •	LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
	LENS-16-FR	Clear/Frosted Lens	Frosted
	LENS-16-SPR	Spread Lens	Spread Lens
	LENS-16-BEL	Beam Elongating Lens	Beam Elongating
	LENS-16-HCL	Honeycomb Louver	Black