

Lotos 2" & Multiples

Adjustable Downlight 3000K

Model	Beam	Color Temp & CRI	Lumens	СВСР	Finish
R2ERAR	W 45°	930 3000K - 90	500		WT White

Example: R2ERAR-W930-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light outputand efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge.

- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Multiple fixture heads with individual adjustability
- · Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling Standards: ETL, cETL, Title 24 JA8 Compliant, Wet Location Listed

Construction Steel with frosted TIR lens



FINISHES:

Fixture Type:


Project:

Location:

Catalog Number:



LINE DRAWING:





WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2025

WAC LIGHTING

Lotos 2" & Multiples

Adjustable Downlight 3000K

Model	Beam	Color Temp & CRI	Lumens	СВСР	Finish
R2ESAR	W 45°	930 3000K - 90	500		WT White

Example: R2ESAR-W930-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light outputand efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel.Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge.

FEATURES

- Multiple LED array for uniform illumination
- · Rotatable multi-axis gimbal ring
- Multiple fixture heads with individual adjustability
- · Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, CETL, Title 24 JA8 Compliant, Wet Location Listed

Construction Steel with frosted TIR lens



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:



White

LINE DRAWING:

_ −Ø1%′



WAC LIGHTING

Lotos 2" & Multiples

Adjustable Downlight 3000K

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2ESAR-2	W 45°	930 3000K - 90	500 x 2		WT White

Example: R2ESAR-2-W930-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light outputand efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge.

FEATURES

- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Multiple fixture heads with individual adjustability
- · Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, CETL, Title 24 JA8 Compliant, Wet Location Listed

Construction Steel with frosted TIR lens



FINISHES:

Fixture Type:

Project:

Location:


Catalog Number:



White

LINE DRAWING:







Lotos 2" & Multiples

Adjustable Downlight 3000K

Model	Beam	Color Temp & CRI	Lumens	СВСР	Finish
R2ESAR-3	W 45°	930 3000K - 90	500 x 3		WT White

Example: R2ESAR-3-W930-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light outputand efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel.Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge.

FEATURES

- Multiple LED array for uniform illumination
- · Rotatable multi-axis gimbal ring
- Multiple fixture heads with individual adjustability
- · Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, CETL, Title 24 JA8 Compliant, Wet Location Listed

Construction Steel with frosted TIR lens



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:



White

LINE DRAWING:

