



FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Wall-glow ambient lighting with diffuser for a finished side view
- Forward-phase dimming technology
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Made in America with U.S. and global components

AVAILABLE OPTIONS

- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000 Kelvin
- Replaceable LEDs
- 695 lumens per foot
- Maximum 100 lumens per watt efficacy
- Calculated L₇₀ 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

PRODUCT DESCRIPTION

A well-balanced shape, sleek lighted border, and soothing wall glow merge together in a breathtaking Trinity™ that promises to bring any space to life.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting as well as wall-glow ambient lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with a greater than or equal to 90 CRI (color rendering index). Product will be made in America with U.S and global components and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Includes multiple ceiling mounting slots and counter mounted anchor
- Chassis should be mounted to wall studs; mounting holes are provided
- Controlled by forward-phase dimming wall switch
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model	Base Model with Keen	Dimensions	Power Requirements
TRI-30	30" diameter x 1.75"D (762mm x 44mm)	120/240 VAC, 57W	TRI-30

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com.

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

