



45359 TRIMLESS ROUND FIXED DOWNLIGHT



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

2 5/8"

TYPE:			
DATE:			
NOTES:			



2700K . 3000K . 3500K . 4000K . 5000K

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. Mesh plate included.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for wet location.

DIMENSIONS

- Cut hole: ø2 5/8". • Fixture: ø3 9/16" x 5"H.
- **ELECTRICAL**
- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F)(-20°C~-40°C).

LIGHT MODULE

- 1 x 15W Integrated LED COB.
- · Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- · Beam angle: 38 degree.
- 27K |30K |35K Kelvin (CCT):
- Delivered Lumen: 882 lm |948 lm |1024 lm |1053 lm |1019 lm

CERTIFICATIONS











140K



ORDERING GUIDE

MODEL	FINISH		
45359-026	Black		
45359-019	White		

ACCESSORIES



45612-015 60" 3 pin Connector



45363-016 **NEW CONSTRUCTION SMASH PLATE** 13 1/4" x 6 1/2" ø2 3/4"

2 9/16'



NO IC BOX REQUIRED

2 1/16"

				BEAM	
UMENS	KELVIN	DIMMABLE	CRI	ANGLE	ADJUSTABLE
to 1053	CCT Selectable	TRIAC/ELV	90+	38°	NO

Driver Box included

Up

WATTS

15W








PRODUCT DIMENSIONS

15/16"




11 1/16"






PHOTOMETRICS


Imperial






Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

Metrics





Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.