



MT-3LD111 - 1 Light

Mini LED Multiple Spots

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box (New Construction): Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: 120VAC Input

Light Source: High output LED (included with housing)


Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 4½" x 4½" cutout.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed; Energy Star rated

			Power	Beam	Color Temp	CRI	Lumens	CBCP	Finish
<p>MT-3LD111NA New Construction Non-IC, Airtight</p> <p>11W</p>	F	25°	927	2700K	90	710	1886	BK	White trim with black interior
			930	3000K	90	785	2176	WT	White trim with white interior
			935	3500K	90	795	2184		
			940	4000K	90	805	2224		
	W	45°	927	2700K	90	705	911	BK	White trim with black interior
			930	3000K	90	775	1015	WT	White trim with white interior
			935	3500K	90	785	1024		
			940	4000K	90	795	1042		
<p>MT-3LD111R Remodel Non-IC</p> <p>11W</p>	F	25°	927	2700K	90	710	1886	BK	White trim with black interior
			930	3000K	90	785	2176	WT	White trim with white interior
			935	3500K	90	795	2184		
			940	4000K	90	805	2224		
	W	45°	927	2700K	90	705	911	BK	White trim with black interior
			930	3000K	90	775	1015	WT	White trim with white interior
			935	3500K	90	785	1024		
			940	4000K	90	795	1042		



Example: **MT-3LD111R-F30-BK**

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760


Phone (800) 526.2588 • Fax (800) 526.2585

MT-3LD211 - 2 Lights

Mini LED Multiple Spots

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box (New Construction): Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: 120VAC Input

Light Source: High output LED (included with housing)


Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 8½" x 4½" cutout.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed; Energy Star rated

		Power	Beam	Color Temp	CRI	Lumens	CBCP	Finish
<p>MT-3LD211NA New Construction Non-IC, Airtight</p> <p>22W</p>	<p>MT-3LD211R Remodel Non-IC</p> <p>22W</p>	22W	F 25°	927 2700K 90 710 x2 1886 x2	90	710 x2 785 x2 795 x2 805 x2	1886 x2 2176 x2 2184 x2 2224 x2	BK White trim with black interior
				930 3000K 90 785 x2 2176 x2				WT White trim with white interior
				935 3500K 90 795 x2 2184 x2				BK White trim with black interior
				940 4000K 90 805 x2 2224 x2				WT White trim with white interior
			W 45°	927 2700K 90 705 x2 911 x2	90	705 x2 775 x2 785 x2 795 x2	911 x2 1015 x2 1024 x2 1042 x2	BK White trim with black interior
				930 3000K 90 775 x2 1015 x2				WT White trim with white interior
				935 3500K 90 785 x2 1024 x2				BK White trim with black interior
				940 4000K 90 795 x2 1042 x2				WT White trim with white interior
			F 25°	927 2700K 90 710 x2 1886 x2	90	710 x2 785 x2 795 x2 805 x2	1886 x2 2176 x2 2184 x2 2224 x2	BK White trim with black interior
				930 3000K 90 785 x2 2176 x2				WT White trim with white interior
				935 3500K 90 795 x2 2184 x2				BK White trim with black interior
				940 4000K 90 805 x2 2224 x2				WT White trim with white interior
			W 45°	927 2700K 90 705 x2 911 x2	90	705 x2 775 x2 785 x2 795 x2	911 x2 1015 x2 1024 x2 1042 x2	BK White trim with black interior
				930 3000K 90 775 x2 1015 x2				WT White trim with white interior
				935 3500K 90 785 x2 1024 x2				BK White trim with black interior
				940 4000K 90 795 x2 1042 x2				WT White trim with white interior



Example: **MT-3LD211R-F30-BK**

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585

MT-3LD311 - 3 Lights

Mini LED Multiple Spots

WAC LIGHTING


Responsible Lighting®

Fixture Type:

Catalog Number:

Project: _____

Location: _____



PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box (New Construction): Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: 120VAC Input

Light Source: High output LED (included with housing)

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 12" x 4½" cutout.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed; Energy Star rated

		Power	Beam	Color Temp	CRI	Lumen	CBCP	Finish
<p>MT-3LD311NA New Construction Non-IC, Airtight</p> <p>33W</p>	F	25°	927	2700K	90	710 x3	1886 x3	BK White trim with black interior
			930	3000K	90	785 x3	2176 x3	WT White trim with white interior
			935	3500K	90	795 x3	2184 x3	
			940	4000K	90	805 x3	2224 x3	
<p>MT-3LD311R Remodel Non-IC</p> <p>33W</p>	W	45°	927	2700K	90	705 x3	911 x3	BK White trim with black interior
			930	3000K	90	775 x3	1015 x3	WT White trim with white interior
			935	3500K	90	785 x3	1024 x3	
			940	4000K	90	795 x3	1042 x3	
<p>MT-3LD311R Remodel Non-IC</p> <p>33W</p>	F	25°	927	2700K	90	710 x3	1886 x3	BK White trim with black interior
			930	3000K	90	785 x3	2176 x3	WT White trim with white interior
			935	3500K	90	795 x3	2184 x3	
			940	4000K	90	805 x3	2224 x3	
<p>MT-3LD311R Remodel Non-IC</p> <p>33W</p>	W	45°	927	2700K	90	705 x3	911 x3	BK White trim with black interior
			930	3000K	90	775 x3	1015 x3	WT White trim with white interior
			935	3500K	90	785 x3	1024 x3	
			940	4000K	90	795 x3	1042 x3	



Example: **MT-3LD311R-F30-BK**

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585