

NLCBC2-45 Series

4" Cobalt Click LED Retrofit Reflectors

Source: 10W or 12W LED
750lm or 1000lm

PRODUCT DESCRIPTION

Cobalt retrofit series is cULus classified for use in existing IC or Non-IC housings manufactured by Nora and others. The 4" retrofit click luminaires product up to 1000 lumen output at 90+ CRI. The Cobalt series integrates a Signify COB family of LED arrays, giving bright spectacular light output and low power consumption.

FEATURES

- 750lm or 1000lm LED output
- 2700K, 3000K, 3500K or 4000K @ 90+ CRI
- Signify COB LED or Comfort Dim technology
- 120V or 120V-277V input voltage
- Includes medium base socket adapter for easy retrofitting in 4" recessed housings
- 5-year limited warranty
- ENERGY STAR certified
- cULus classified for wet locations

SPECIFICATION

Trim: UTM thermal management features an integral driver, large heat sink and the latest COB technology. The patented "Click" system allows the aluminum spun trims to be easily changed in the field with the help of spring mounting clips which properly secure them to the LED module.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 4" housings.

Retrofit: Cobalt retrofit series includes medium base screw-socket adapter ([NRA-211SM](#)) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify [NRA-212SM](#).

ELECTRICAL

Input Voltage: 120V or 120V-277V, must specify

Lumens / Wattage: 750lm / 10W or 1000lm / 12W

Color Temperature: 2700K, 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Operating Temperature: 0°C to 25°C

Lifetime: 50,000 hours @ L70

Comfort Dim: Comfort Dim color tunes the temperature from a bright 3100K, to a romantic and comfortable 1700K on a gradual, even curve.

Dimming: Available in Triac/ELV/0-10V, must specify

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Cobalt retrofit reflectors are compatible with most 4" IC and Non-IC housings by Nora and others.

Fire Box

[NFBIC-4LMRATA*](#)

[NFBIC-4LMRATA/4W*](#)

[NFBIC-4INCATA](#)

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Line Voltage

New Construction

[NHIC-4LMRAT*](#)

[NHIC-4LMRAT/4W*](#)

[NHIC-4LMRAT/EM*](#)

[NHIC-4LMRAT/6WEM*](#)

[NHIC-4LMRAT/277*](#)

(includes step-down transformer)

[NHICCP-4LMRAT*](#)

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Dedicated LED for EM

ICAT Dedicated LED for EM+LE4

ICAT Dedicated LED, 277V

Chicago Plenum Dedicated LED

ICAT Line Voltage

AT Line Voltage

ICAT GU24

Remodel

[NHRIC-4LMRAT*](#)

[NSRIC-4040AT](#)

[NSR-4040AT](#)

[NHRIC-4G24AT](#)

ICAT Dedicated LED

ICAT Line Voltage

AT Line Voltage

ICAT GU24

* Nora Dedicated LED housings are cULus listed for use only with Nora LED Retrofits.

ACCESSORIES

[NLCBC-4EYELID](#): Round eyelid used to convert round reflector or baffle to half moon wall wash trim.

[NLCBC-4OR](#): Round oversize ring used to cover ceiling cut-outs up to 5-3/4".

LABELS AND LISTINGS

- cULus classified for Wet Locations
- ENERGY STAR certified (not black, bronze or copper)
- 5-Year Limited Warranty
- Meets ASTM-E283 Air-Tight requirements
- Patent #D797,977S; D871,644S; D824,568S
- Certified to the high efficacy requirements of California Title 24 JA8-2022



Type

Project

Catalog No.

Notes

PRODUCT IMAGES & DIMENSIONS



4" Cobalt Click LED Retrofit Reflectors

Reflector Type	Color Temp.	Finish (see chart below)	Lumens / Wattage	Dimming & Emergency
NLCBC2-451 = Round Reflector	27 = 2700K	BB = Black / Black	/A = 750lm / 10W	(blank) = 120V Triac/ELV
NLCBC2-452 = Round Baffle	30 = 3000K	BW = Black / White	/10 = 1000lm / 12W	EM = Remote Emergency (requires Nora EM housing)
NLCBC2-453 = Square Round	35 = 3500K	BZBZ = Bronze / Bronze		LE4 = 120V 0-10V/Triac/ELV 277V 0-10V (req. Nora 4W housing)
NLCBC2-455 = Square Pinhole	40 = 4000K	DW = Diffused / White		LE4EM = LE4 w/ Remote Emergency (requires Nora 6WEM housing)
NLCBC2-456 = Square Regress	CD = Comfort Dim [†]	HZW = Haze / White		
		MPW = Matte Powder White		
		NN = Natural Metal / Nat. Metal		
		PW = Pewter / White		
		WW = White / White		

[†] Comfort Dim technology available in 750lm & 120V only

Optional Accessories

Description
NLCBC-4EYELIDB = 4" Round Eyelid, Black
NLCBC-4EYELIDBZ = 4" Round Eyelid, Bronze
NLCBC-4EYELIDMPW = 4" Round Eyelid, Matte Powder White
NLCBC-4EYELIDW = 4" Round Eyelid, White
NLCBC-4OR-B = 4" Round Oversize Ring, Black
NLCBC-4OR-BZ = 4" Round Oversize Ring, Bronze
NLCBC-4OR-MPW = 4" Round Oversize Ring, Matte Powder White
NLCBC-4OR-W = 4" Round Oversize Ring, White
NRA-211SM = Medium base screw-in socket (included)
NRA-212SM = Socket adapter for use with GU24 housings

Example: **NLCBC2-45130MPW/A** = 4" Cobalt Click LED Retrofit Reflector, 750lm / 10W LED, 3000K, Matte Powder White Finish

PHOTOMETRICS

4" Cobalt Click Retrofit Series

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR1294
Part Number: NLCBC2-45127WW/A
Beam Spread: 98° Wide Flood
Lumens: 819lm
Wattage: 9.44W
Efficacy: 87lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	23.9fc	9'-4"
6'	10.6fc	13'-11"
8'	6fc	18'-6"
10'	3.8fc	23'-1"
12'	2.7fc	27'-10"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	283	34.6
0-40	455	55.6
0-60	743	90.8
0-90	816	99.6
90-180	4	0.4
0-180	819	100

Candela Table

Vertical Angles	Candela
0	382
5	381
15	357
25	319
35	276
45	223

Test Information

Test Number: NTR1300
Part Number: NLCBC2-45127WW/10
Beam Spread: 98° Wide Flood
Lumens: 978lm
Wattage: 11.56W
Efficacy: 85lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	28.4fc	9'-4"
6'	12.6fc	13'-11"
8'	7.1fc	18'-6"
10'	4.5fc	23'-2"
12'	3.2fc	27'-10"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	336	34.3
0-40	540	55.2
0-60	886	90.7
0-90	975	99.7
90-180	3	0.3
0-180	978	100

Candela Table

Vertical Angles	Candela
0	454
5	450
15	422
25	378
35	329
45	266

Test Information

Test Number: NTR1295
Part Number: NLCBC2-45130WW/A
Beam Spread: 99° Wide Flood
Lumens: 783lm
Wattage: 9.49W
Efficacy: 83lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	22.5fc	9'-6"
6'	10fc	14'-4"
8'	5.6fc	19'
10'	3.6fc	23'-10"
12'	2.5fc	28'-7"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	267	34.1
0-40	430	54.8
0-60	711	90.7
0-90	782	99.8
90-180	2	0.2
0-180	783	100

Candela Table

Vertical Angles	Candela
0	360
5	357
15	335
25	300
35	259
45	211

Test Information

Test Number: NTR1301
Part Number: NLCBC2-45130WW/10
Beam Spread: 99° Wide Flood
Lumens: 924lm
Wattage: 11.43W
Efficacy: 81lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.18
Spacing Criteria (90°-270): 1.18



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	26.7fc	9'-4"
6'	11.9fc	14'
8'	6.7fc	18'-7"
10'	4.3fc	23'-4"
12'	3fc	28'

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	317	34.3
0-40	509	55.1
0-60	837	90.6
0-90	920	99.5
90-180	5	0.5
0-180	924	100

Candela Table

Vertical Angles	Candela
0	427
5	424
15	398
25	356
35	307
45	248

NLCBC2-55 Series

5" Cobalt Click LED Retrofit Reflectors

Source: 12W LED

750lm or 1000lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Cobalt retrofit series is cULus classified for use in existing IC or Non-IC housings manufactured by Nora and others. The 5" retrofit click luminaires produce up to 1000 lumen output at 90+ CRI. The Cobalt series integrates an array of COB LEDs, giving bright spectacular light output and low power consumption.

FEATURES

- 750lm or 1000lm LED output
- 2700K, 3000K, 3500K or 4000K @ 90+ CRI
- COB LED or Comfort Dim technology
- 120V or 120V-277V input voltage
- Includes medium base socket adapter for easy retrofitting in 5" recessed housings
- 5-year limited warranty
- ENERGY STAR certified
- cULus classified for wet locations

SPECIFICATION

Trim: UTM thermal management features an integral driver, large heat sink and the latest COB technology. The patented "Click" system allows the aluminum spun trims to be easily changed in the field with the help of spring mounting clips which properly secure them to the LED module.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 5" housings.

Retrofit: Cobalt retrofit series includes medium base screw-socket adapter (NRA-211SM) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify [NRA-212SM](#).

ELECTRICAL

Input Voltage: 120V or 120V-277V, must specify

Lumens / Wattage: 750lm / 12W or 1000lm / 12W

Color Temperature: 2700K, 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Operating Temperature: 0-35°C

Lifetime: 50,000 hours @ L70

Comfort Dim: Comfort Dim color tunes the temperature from a bright 3100K, to a romantic and comfortable 1700K on a gradual, even curve.

Dimming: Available in Triac/ELV/0-10V, must specify

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Cobalt retrofit reflectors are compatible with most 5" IC and Non-IC housings by Nora and others.

Fire Box

[NFBIC-5LMRATA*](#)

[NFBIC-5LMRATA/4W*](#)

[NFBIC-5INCATA](#)

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Line Voltage

New Construction

[NHIC-527LMRAT*](#)

[NHIC-5LMRAT*](#)

[NHIC-5LMRAT/4W*](#)

[NHIC-5LMRAT/EM*](#)

[NHIC-5LMRAT/6WEM*](#)

[NHIC-5LMRAT/277*](#)

(includes step-down transformer)

[NHIC-527OAT](#)

[NHIC-501OAT](#)

[NH-501Q](#)

[NHIC-5G24ATFL](#)

Shallow ICAT Dedicated LED

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Dedicated LED for EM

ICAT Dedicated LED for EM+LE4

ICAT Dedicated LED, 277V

Shallow ICAT Line Voltage

ICAT Line Voltage

Non-IC Line Voltage

ICAT GU24

Remodel

[NHRIC-527LMRAT*](#)

[NHRIC-5LMRAT*](#)

[NHRIC-527OAT](#)

[NHRIC-504OAT](#)

[NHR-504Q](#)

Shallow ICAT Dedicated LED

ICAT Dedicated LED

Shallow ICAT Line Voltage

ICAT Line Voltage

Non-IC Line Voltage

* Nora Dedicated LED housings are cULus listed for use only with Nora LED Retrofits.

ACCESSORIES

NLCBC-5EYELID: Round eyelid used to convert round reflector or baffle to half moon wall wash trim.

NLCBC-5OR: Round oversize ring used to cover ceiling cut-outs up to 7".

LABELS AND LISTINGS

- cULus classified for Wet Locations
- ENERGY STAR certified (not black, bronze or copper)
- 5-Year Limited Warranty
- Meets ASTM-E283 Air-Tight requirements
- Patent #D797,977S; D871,644S; D824,568S
- Certified to the high efficacy requirements of California Title 24 JA8-2022




PRODUCT IMAGES & DIMENSIONS




NLCBC2-551

Round Open Reflector




NLCBC2-552

Round Open Baffle




NLCBC2-553

Square Reflector w/ Round Aperture



NLCBC2-556

Square Reflector w/ Square Aperture



5" Cobalt Click LED Retrofit Reflectors

Reflector Type	Color Temp.	Finish (see chart below)	Lumens / Wattage	Dimming & Emergency
NLCBC2-551 = Round Reflector	27 = 2700K	BB = Black / Black	(blank) = 750lm / 12W	(blank) = 120V Triac/ELV
NLCBC2-552 = Round Baffle	30 = 3000K	BW = Black / White	/10 = 1000lm / 12W	EM = Remote Emergency
NLCBC2-553 = Square Round	35 = 3500K	BZBZ = Bronze / Bronze		(requires Nora EM housing)
NLCBC2-556 = Square Regress	40 = 4000K	COCO = Copper / Copper		LE4 = 120V 0-10V/Triac/ELV
	CD = Comfort Dim ¹	DW = Diffused / White		277V 0-10V (req. Nora 4W housing)
		HZW = Haze / White		LE4EM = LE4 w/ Remote Emergency
		MPW = Matte Powder White		(requires Nora 6WEM housing)
		NN = Natural Metal / Nat. Metal		
		PW = Pewter / White		
		WW = White / White		

¹ Comfort Dim technology available in 750lm & 120V only

Available Finishes

	BB	BW	BZBZ	COCO	DW	HZW	MPW	NN	PW	WW
551	•		•	•	•	•	•	•		•
552	•		•				•	•		•
553			•		•	•	•	•		•
556	•	•	•			•	•	•	•	•

Optional Accessories

Description
NLCBC-5EYELIDB = 5" Round Eyelid, Black
NLCBC-5EYELIDBZ = 5" Round Eyelid, Bronze
NLCBC-5EYELIDMPW = 5" Round Eyelid, Matte Powder White
NLCBC-5EYELIDW = 5" Round Eyelid, White
NLCBC-5OR-B = 5" Round Oversize Ring, Black
NLCBC-5OR-BZ = 5" Round Oversize Ring, Bronze
NLCBC-5OR-MPW = 5" Round Oversize Ring, Matte Powder White
NLCBC-5OR-W = 5" Round Oversize Ring, White
NRA-211SM = Medium base screw-in socket (included)
NRA-212SM = Socket adapter for use with GU24 housings

PHOTOMETRICS

5" Cobalt Click Retrofit Series

750 lumens

Type

Project

Catalog No.

Notes

Test Information

Test Number: 795866

Part Number: NLCBC2-55130WWLE4

Lumens: 892lm


Wattage: 12.1W

Efficacy: 74lpw

CCT / CRI: 3000K / 90 CRI

Spacing Criteria (0°-180): 1.18

Spacing Criteria (90°-270): 1.2



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	25.7fc	9'-6"
6'	11.4fc	14'-2"
8'	6.4fc	18'-11"
10'	4.1fc	23'-8"
12'	2.9fc	28'-5"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	306	34.3
0-40	495	55.5
0-60	817	91.6
0-90	889	99.7
90-180	3	0.3
0-180	892	100

Candela Table

Vertical Angles	Candela
0	411
5	407
15	383
25	345
35	301
45	244

Test Information

Test Number: 795866

Part Number: NLCBC2-55230WWLE4

Lumens: 888lm


Wattage: 12.1W

Efficacy: 74lpw

CCT / CRI: 3000K / 90 CRI

Spacing Criteria (0°-180): 1.24

Spacing Criteria (90°-270): 1.24



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	24fc	10'-1"
6'	10.7fc	15'-1"
8'	6fc	20'-1"
10'	3.9fc	25'-2"
12'	2.7fc	30'-2"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	294	33.1
0-40	480	54
0-60	806	90.7
0-90	885	99.7
90-180	3	0.3
0-180	888	100

Candela Table

Vertical Angles	Candela
0	385
5	381
15	365
25	335
35	296
45	243

Test Information

Test Number: 795866

Part Number: NLCBC2-55330WWLE4

Lumens: 870lm


Wattage: 12.1W

Efficacy: 72lpw

CCT / CRI: 3000K / 90 CRI

Spacing Criteria (0°-180): 1.22

Spacing Criteria (90°-270): 1.24



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	24.9fc	9'-2"
6'	11.1fc	13'-10"
8'	6.2fc	18'-5"
10'	4fc	23'
12'	2.8fc	27'-8"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	304	35
0-40	492	56.6
0-60	792	91.1
0-90	867	99.8
90-180	2	0.2
0-180	870	100

Candela Table

Vertical Angles	Candela
0	398
5	395
15	378
25	345
35	301
45	236

Test Information

Test Number: 795866

Part Number: NLCBC2-55630WWLE4

Lumens: 777lm


Wattage: 12.1W

Efficacy: 64lpw

CCT / CRI: 3000K / 90 CRI

Spacing Criteria (0°-180): 1.18

Spacing Criteria (90°-270): 1.2



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	24.2fc	7'-8"
6'	10.8fc	11'-6"
8'	6.1fc	15'-4"
10'	3.9fc	19'-2"
12'	2.7fc	23'

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	293	37.7
0-40	466	59.9
0-60	697	89.8
0-90	755	97.2
90-180	22	2.8
0-180	777	100

Candela Table

Vertical Angles	Candela
0	388
5	384
15	367
25	332
35	273
45	180

PHOTOMETRICS

5" Cobalt Click Retrofit Series

1000 lumens

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR1302
Part Number: NLCBC2-55127WW/10
Beam Spread: 101° Wide Flood
Lumens: 1008lm
Wattage: 11.44W
Efficacy: 88lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.2
Spacing Criteria (90°-270): 1.2



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	28fc	9'-8"
6'	12.4fc	14'-7"
8'	7fc	19'-6"
10'	4.5fc	24'-4"
12'	3.1fc	29'-2"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	336	33.3
0-40	543	53.9
0-60	906	89.9
0-90	1002	99.4
90-180	6	0.6
0-180	1008	100

Candela Table

Vertical Angles	Candela
0	448
5	445
15	420
25	379
35	331
45	272

Test Information

Test Number: NTR1303
Part Number: NLCBC2-55130WW/10
Beam Spread: 101° Wide Flood
Lumens: 965lm
Wattage: 11.41W
Efficacy: 85lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.2
Spacing Criteria (90°-270): 1.2



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	26.9fc	9'-8"
6'	12fc	14'-7"
8'	6.7fc	19'-5"
10'	4.3fc	24'-4"
12'	3fc	29'-1"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	322	33.4
0-40	519	53.8
0-60	865	89.7
0-90	956	99.1
90-180	9	0.9
0-180	965	100

Candela Table

Vertical Angles	Candela
0	430
5	427
15	404
25	363
35	315
45	259

NLCBC2-65 Series

6" Cobalt Click LED Retrofit Reflectors

Source: 10W or 12W LED

750lm or 1000lm

PRODUCT DESCRIPTION

Cobalt retrofit series is cULus classified for use in existing IC or Non-IC housings manufactured by Nora and others. The 6" retrofit click luminaires product up to 1000 lumen output at 90+ CRI. The Cobalt series integrates a Signify COB family of LED arrays, giving bright spectacular light output and low power consumption.

FEATURES

- 750lm or 1000lm LED output
- 2700K, 3000K, 3500K or 4000K @ 90+ CRI
- Signify COB LED or Comfort Dim technology
- 120V or 120V-277V input voltage
- Includes medium base socket adapter for easy retrofitting in 6" recessed housings
- 5-year limited warranty
- ENERGY STAR certified
- cULus classified for wet locations

SPECIFICATION

Trim: UTM thermal management features an integral driver, large heat sink and the latest COB technology. The patented "Click" system allows the aluminum spun trims to be easily changed in the field with the help of spring mounting clips which properly secure them to the LED module.

Mounting: Two steel, spring mounting blades allow for easy and secure mounting in most 6" housings.

Retrofit: Cobalt retrofit series includes medium base screw-socket adapter ([NRA-211SM](#)) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify [NRA-212SM](#).

ELECTRICAL

Input Voltage: 120V or 120V-277V, must specify

Lumens / Wattage: 750lm / 10W or 1000lm / 12W

Color Temperature: 2700K, 3000K, 3500K or 4000K

Color Rendering Index: 90+ CRI

Operating Temperature: 0-35°C

Lifetime: 50,000 hours @ L70

Comfort Dim: Comfort Dim color tunes the temperature from a bright 3100K, to a romantic and comfortable 1700K on a gradual, even curve.

Dimming: Available in Triac/ELV/0-10V, must specify

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Cobalt retrofit reflectors are compatible with most 6" IC and Non-IC housings by Nora and others.

Fire Box

[NFBIC-6LMRATA*](#)

[NFBIC-6LMRATA/4W*](#)

[NFBIC-6INCATA](#)

New Construction

[NHIC-27LMRAT*](#)

[NHIC-6LMRAT*](#)

[NHIC-6LMRAT/4W*](#)

[NHIC-6LMRAT/EM*](#)

[NHIC-6LMRAT/6WEM*](#)

[NHIC-6LMRAT/277*](#)

(includes step-down transformer)

[NHICCP-6LMRAT*](#)

[NHIC-27OAT](#)

[NHIC-17OAT](#)

[NH-260](#)

[NHIC-6G24ATFL](#)

Remodel

[NHRIC-27LMRAT*](#)

[NHRIC-6LMRAT*](#)

[NHRIC-27OAT](#)

[NHRIC-17OAT](#)

[NHR-260](#)

* Nora Dedicated LED housings are cULus listed for use only with Nora LED Retrofits.

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Line Voltage

Shallow ICAT Dedicated LED

ICAT Dedicated LED

ICAT Dedicated LED for LE4

ICAT Dedicated LED for EM

ICAT Dedicated LED for EM+LE4

ICAT Dedicated LED, 277V

(includes step-down transformer)

Chicago Plenum Dedicated LED

Shallow ICAT Line Voltage

ICAT Line Voltage

Non-IC Line Voltage

ICAT GU24

Shallow ICAT Dedicated LED

ICAT Dedicated LED

Shallow ICAT Line Voltage

ICAT Line Voltage

Non-IC Line Voltage

ACCESSORIES

[NLCBC-6EYELID](#): Round eyelid used to convert round reflector or baffle to half moon wall wash trim.

[NLCBC-6OR](#): Round oversize ring used to cover ceiling cut-outs up to 8".

LABELS AND LISTINGS

- cULus classified for Wet Locations
- ENERGY STAR certified (not black, bronze or copper)
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- Patent #D797,977S; D871,644S; D824,568S
- Certified to the high efficacy requirements of California Title 24 JA8-2022







Type

Project

Catalog No.

Notes

PRODUCT IMAGES & DIMENSIONS



6" Cobalt Click LED Retrofit Reflectors

Reflector Type	Color Temp.	Finish (see chart below)	Lumens / Wattage	Dimming & Emergency
NLCBC2-651 = Round Reflector	27 = 2700K	BB = Black / Black	/A = 750lm / 10W	(blank) = 120V Triac/ELV
NLCBC2-652 = Round Baffle	30 = 3000K	BW = Black / White	/10 = 1000lm / 12W	EM = Remote Emergency (requires Nora EM housing)
NLCBC2-653 = Square Round	35 = 3500K	BZBZ = Bronze / Bronze		LE4 = 120V 0-10V/Triac/ELV 277V 0-10V (req. Nora 4W housing)
NLCBC2-656 = Square Regress	40 = 4000K	COCO = Copper / Copper		LE4EM = LE4 w/ Remote Emergency (requires Nora 6WEM housing)
	CD = Comfort Dim ¹	DW = Diffused / White		
		HZMPW = Haze / Matte Powder White		
		HZW = Haze / White		
		MPW = Matte Powder White		
		NN = Natural Metal / Nat. Metal		
		PW = Pewter / White		
		WW = White / White		

¹ Comfort Dim technology available in 750lm & 120V only

Available Finishes

	BB	BW	BZBZ	COCO	DW	HZMPW	HZW	MPW	NN	PW	WW
651	*	*	*	*	*	*	*	*	*	*	*
652	*	*	*	*	*	*	*	*	*	*	*
653	*	*	*	*	*	*	*	*	*	*	*
656	*	*	*	*	*	*	*	*	*	*	*

Optional Accessories

Description
NLCBC-6EYELIDB = 6" Round Eyelid, Black
NLCBC-6EYELIDBZ = 6" Round Eyelid, Bronze
NLCBC-6EYELIDMPW = 6" Round Eyelid, Matte Powder White
NLCBC-6EYELIDW = 6" Round Eyelid, White
NLCBC-6OR-B = 6" Round Oversize Ring, Black
NLCBC-6OR-BZ = 6" Round Oversize Ring, Bronze
NLCBC-6OR-MPW = 6" Round Oversize Ring, Matte Powder White
NLCBC-6OR-W = 6" Round Oversize Ring, White
NRA-211SM = Medium base screw-in socket (included)
NRA-212SM = Socket adapter for use with GU24 housings

Example: NLCBC2-65130MPW/A = 6" Cobalt Click LED Retrofit Reflector, 750lm / 10W LED, 3000K, Matte Powder White Finish

PHOTOMETRICS

6" Cobalt Click Retrofit Series

Type


Project

Catalog No.

Notes

Test Information

Test Number: NTR1298
Part Number: NLCBC2-65127WW/A
Beam Spread: 95° Wide Flood
Lumens: 844lm
Wattage: 9.56W
Efficacy: 88lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.14
Spacing Criteria (90°-270): 1.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	25.8fc	8'-10"
6'	11.5fc	13'-1"
8'	6.5fc	17'-6"
10'	4.1fc	21'-11"
12'	2.9fc	26'-4"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	301	35.7
0-40	481	57
0-60	770	91.2
0-90	839	99.5
90-180	4	0.5
0-180	844	100

Candela Table

Vertical Angles	Candela
0	413
5	409
15	381
25	336
35	287
45	227

Test Information

Test Number: NTR1304
Part Number: NLCBC2-65127WW/10
Beam Spread: 95° Wide Flood
Lumens: 1006lm
Wattage: 11.58W
Efficacy: 87lpw
CCT / CRI: 2700K / 90 CRI
Spacing Criteria (0°-180): 1.14
Spacing Criteria (90°-270): 1.14



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	30.8fc	8'-8"
6'	13.7fc	13'-1"
8'	7.7fc	17'-6"
10'	4.9fc	21'-10"
12'	3.4fc	26'-2"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	359	35.7
0-40	573	57
0-60	917	91.2
0-90	1001	99.5
90-180	5	0.5
0-180	1006	100

Candela Table

Vertical Angles	Candela
0	492
5	487
15	456
25	403
35	343
45	273

Test Information

Test Number: NTR1299
Part Number: NLCBC2-65130WW/A
Beam Spread: 101° Wide Flood
Lumens: 857lm
Wattage: 9.54W
Efficacy: 90lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.22
Spacing Criteria (90°-270): 1.22



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	23.7fc	9'-8"
6'	10.5fc	14'-7"
8'	5.9fc	19'-5"
10'	3.8fc	24'-4"
12'	2.6fc	29'-2"

Zonal Lumen Summary


Zone	Lumens	% Luminaire
0-30	289	33.7
0-40	468	54.6
0-60	774	90.4
0-90	853	99.5
90-180	4	0.5
0-180	857	100

Candela Table

Vertical Angles	Candela
0	379
5	378
15	361
25	330
35	289
45	234

Test Information

Test Number: NTR1305
Part Number: NLCBC2-65130WW/10
Beam Spread: 101° Wide Flood
Lumens: 1021lm
Wattage: 11.35W
Efficacy: 90lpw
CCT / CRI: 3000K / 90 CRI
Spacing Criteria (0°-180): 1.22
Spacing Criteria (90°-270): 1.22



Illuminance at a Distance

Distance from Luminaire	FC at Nadir	Beam Diameter
4'	28fc	9'-10"
6'	12.4fc	14'-8"
8'	7fc	19'-7"
10'	4.5fc	24'-6"
12'	3.1fc	29'-5"

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	341	33.4
0-40	553	54.1
0-60	918	89.9
0-90	1013	99.2
90-180	8	0.8
0-180	1021	100

Candela Table

Vertical Angles	Candela
0	448
5	446
15	427
25	388
35	341
45	278