

# NS-45

## 4" Metal Trim with 1" Pinhole

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Metal trim with 1" pinhole.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE LAMP / HOUSINGS

**Line Voltage:**

50W R20/PAR20 max. (NS-401QAT; NSIC-401QAT; NSR-404QAT; NSRIC-404QAT)


See individual housing specification sheets for more information.

### LABELS AND LISTINGS

\* cULus Listed for Damp Location when used with compatible housing



### PRODUCT IMAGES & DIMENSIONS




**NS-45**



**NS-45CO**



**NS-45N**



### 4" Metal Trim with 1" Pinhole

Catalog No.

**NS-45** = 4" White Metal Trim with 1" Pinhole

**NS-45CO** = 4" Copper Metal Trim with 1" Pinhole

**NS-45N** = 4" Natural Metal Trim with 1" Pinhole

### Compatible Housings

Catalog No.

**NS-401QAT** = Non-IC Air-Tight New Construction / 50W max

**NSIC-401QAT** = IC Air-Tight New Construction / 50W max

**NSR-404QAT** = Non-IC Air-Tight Remodel / 50W max

**NSRIC-404QAT** = IC Air-Tight Remodel / 50W max

Example: **NS-45** = 4" White Metal Trim with 1" Pinhole