

Parallax

Bathroom Vanity

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-73117 18"	2700K	BK Black	6W	263	185
	3000K	BN Brushed Nickel	6W	263	189
	3500K	CH Chrome	6W	263	191

Example: WS-73117-35-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

A high-functioning selection. Unparalleled

FEATURES

- Downlight illumination
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 3000K,2700K,3500K

 Input:
 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8 Compliant

Damp Location Listed


Construction: Aluminum body, PC diffuser



FINISHES:



LINE DRAWING:





Parallax

Bathroom Vanity

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-73123 24"	2700K	BK Black	11W	542	364
	3000K	BN Brushed Nickel	11W	542	377
	3500K	CH Chrome	11W	542	378

Example: WS-73123-35-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

A high-functioning selection. Unparalleled

FEATURES

- Downlight illumination
- Conversion plate included to accommodate 4" junction box
- 3CCT (2700K/3000K/3500K) selectable switch
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 2700K,3500K,3000K

 Input:
 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8 Compliant

Damp Location Listed


Construction: Aluminum body, PC diffuser



FINISHES:



LINE DRAWING:



WS-73123