


DESCRIPTION

Angle Display Sign is a high grade extruded slim aluminum profile that may be mounted from a wall or ceiling and features a lambertian white diffuser that provides uniform light without hotspots. The 95+ CRI fixture is powered by a 24VDC Class 2 Remote Power Supply up to 40' away or a small ELV 60 watt Power Supply that fits in the Junction Box at the Wall or Ceiling. It may be ordered with a 4.6" round or square canopy that fits on a standard 4" square electrical box with round plaster ring. It may also be ordered with 2.8" square canopy or a special feed-thru stem for floating signs. Hinges on the fixture arm rotate up to 90° (from facing the wall to straight down). Available from 12"-120" length and may be ordered in 3, 5, 8, 10 or 12" increments. Fixtures includes 5 year warranty.

FINISHES



Antique Bronze **BZ** Satin Nickel **SN**



APPLICATIONS

Indoor damp or dry locations only. Wall or Ceiling mount used for Hospitality, Retail, and Residential.

LAMP

WATTS PER FOOT	7W (7.5 watts)					
COLOR TEMPERATURE	22K	27K	30K	35K	40K	57K
LUMENS PER FOOT (lm/ft)	36	36	36	36	36	36
LUMENS PER WATT (lm/w)	270	270	270	270	270	270
CRI	85+	95+	95+	85+	85+	85+

50,000 hour lamp life


REMOTE POWER SUPPLIES* & DIMMERS (SOLD SEPARATELY):

24VDC, Class 2 wiring

- [UNI Driver: Universal Dimming \(TRIAC, ELV, 0-10V\)](#)
- [Electronic Low Voltage \(ELV\)[†] 50W](#) (fits inside junction box)

*In-Wall Mounting and drop ceiling Kits available for select power supplies

[†]ELV power supplies are not compatible with nLight, use only Universal power supplies



System	Wattage	Nominal Length in Inches	Canopy	Power Feed	Stem Length	Color Temperature	Finish
AD	7W	120	4P	L	12	27K	SN
AD Angle Display	7W 7.5 Watts,	12-120 Order in 12" increments up to 120" May be ordered in 3, 5, 8 or 10" increments	2SQ 2.8" Square 4RD 4.6" Round 4SQ 4.6" Square FTP Feed-Through Power Stem	L Left Power Feed R Right Power Feed C Center Power Feed	4 4" Stem from Wall or Ceiling 6 6" Stem from Wall or Ceiling 12 12" Stem from Wall or Ceiling 18 18" Stem from Wall or Ceiling	27K 2700K Incandescent 30K 3000K Warm White	BZ Antique Bronze SN Satin Nickel XX Custom Finish, please specify (Must be quoted prior to ordering)

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------



ANGLE DISPLAY SIGN

24VDC SYSTEM



APPLICATION


0-10V dimming for Angle Display Sign

POWER SUPPLY

Class 2, 24VDC output: 120VAC input, Uni Driver

DIMMING

Dimmable with 0-10V dimmer using power supplies above: Philips Sunrise SR1200ZTUNV, 0-10V dimmer recommended.



ANGLE DISPLAY 14' FROM WALL 3000K


7 Watts	
Distance	Foot Candles
1'	91
2'	52
3'	28
4'	22
5'	14
6'	11
7'	9
8'	5

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--



ANGLE DISPLAY SIGN

24VDC SYSTEM



LENGTH CHART Actual lengths for Angle Display

ORDERING-CODE(NOMINALSIZE)	LENGTH(INCHES)	STEMQUANTITY	STEM SPACING (A)	ORDERING-CODE(NOMINALSIZE)	LENGTH(INCHES)	STEMQUANTITY	STEM SPACING (A)
12"	13.1	2	8.1	68"	68.3	3	31.65
15"	15.5	2	10.5	70"	70.7	3	32.85
17"	17.9	2	12.9	72"	73.1	3	34.05
20"	20.3	2	15.3	75"	75.5	3	35.25
22"	22.7	2	17.7	77"	77.9	3	36.45
24"	25.1	2	20.1	80"	80.3	3	37.65
27"	27.5	2	22.5	82"	82.7	3	38.85
29"	29.9	2	24.9	84"	85.1	3	40.05
32"	32.3	2	27.3	87"	87.5	3	41.25
34"	34.7	2	29.7	89"	89.9	3	42.45
36"	37.1	2	32.1	92"	92.3	3	43.65
39"	39.5	2	34.5	94"	94.7	3	44.85
41"	41.9	2	36.9	96"	97.1	3	46.05
44"	44.3	2	39.3	99"	99.5	4	31.5
46"	46.7	2	41.7	101"	101.9	4	32.3
48"	49.1	2	44.1	104"	104.3	4	33.1
51"	51.5	3	23.25	106"	106.7	4	33.9
53"	53.9	3	24.45	108"	109.1	4	34.7
56"	56.3	3	25.65	111"	111.5	4	35.5
58"	58.7	3	26.85	113"	113.9	4	36.3
60"	61.1	3	28.05	116"	116.3	4	37.1
63"	63.5	3	29.25	118"	118.7	4	37.9
65"	65.9	3	30.45	120"	121.1	4	38.7

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--