

PURE SMART TRUCOLOR™ MR16-GU5.3-4W-XWF-RGBTW

12V, 4 WATT WI-FI ENABLED SMART LAMP





REV 12.20.23



DESCRIPTION

The Pure Smart Wi-Fi enabled MR16, GU5.3 base lamp uses TruColor™ RGBTW Technology – With 5 channels (Red, Green, and Blue + Tunable White) of proprietary color mixing we create over 16 million vivid saturated colors and pastels along with 85,000 tunable white tones. Promote a healthy Circadian rhythm and experience the beauty of natural light in its purest form. Tunable White ranges from 1500K to 6500K. Bring out the best of your world by saturating it in 97+ CRI light with TruColor™ Technology. Dial in just the right ambiance for any occasion just by changing the preset color mode. Harness the beauty of the sunset and paint your living room with the amber glow of the golden hour. Experience life in TruColor™.

- Controls Easily control from anywhere with the WiZ app or with the WiZ Pro Dashboard on your computer. At home, experience the convenience of voice control with Alexa or Google Home. Take control to the next level by utilizing the available wall controls.
- Wall Controller On/Off, Dimming, CCT selection, and scene control.
 Must use Pure Smart CWW-TW-SCENE-WH wall controller or Wall/Table
 Battery Remote Controller CWR-TW-SCENE-WH (Sold Separately).
- WiZ SpaceSense[™] Wi-Fi sensing technology that detects motion from disruptions in the Wi-Fi signal and triggers the lights to turn on or off when you enter or exit the room.
- Schedule & Automation Customizable schedules, circadian rhythm, vacation mode, energy monitoring, and predictive maintenance.
- Wi-Fi/Bluetooth Easily setup over Wi-Fi or Bluetooth. No hub required.
- 3rd party log-in and cloud security provide a safe and protected connection. WiZ does not store nor share any personal information.

For custom quotes and layout assistance, send your drawings and ideas to our design team: design@PureEdgeLighting.com.

SMART DIMMING & CONTROLS (SOLD SEPARATELY)

- Pure Smart[™] 5 Channel Wi-Fi Controller
- Pure Smart™ Battery Operated Remote Wi-Fi Controller

SPECIFICATIONS

	000	
	APP	WiZ Mobile App
	WI-FI/BLUETOOTH	Easily setup over Wi-Fi or Bluetooth.
		No hub required. 2.4GHz 802.11b/g/n
		WPA3 Personal
	BULB SHAPE	MR16
	BASE TYPE	GU5.3
	WATTAGE	4 Watts
	WATTAGE EQUIVALENCY	40 watt Incandescent, 28 watt Halogen
	INPUT VOLTAGE	12 Volts AC
	FREQUENCY	60 Hz
	COLOR TEMPERATURE	RGBTW: Red, Blue. Green, Tunable White
		from 1500K-6500K
	LUMENS	386 Lumens at 3000K
	CRI	97 CRI at 3000K
	EFFICACY	94 lumens per watt
	DUV	.0003 average across 2000K-5500K
	RF	92 average across 2000K-5500K
	RG	102 average across 2000K-5500K
	R9	84 average across 2000K-5500K
	SCHEDULES & AUTOMATION	Customizable schedules, circadian
		rhythm, vacation mode, energy
		monitoring, and predictive maintenance
	LOCATION	Indoor, damp location. Suitable for use in
		enclosed and open fixtures
	MATERIAL	Polycarbonate
	OPTICAL	Frosted Lens
	L70 LIFESPAN	30,000 Hours
	TITLE 20 COMPLIANCE	Meets Title 20 regulations and standards
		for efficiency. Suitable for use in California
	WARRANTY	3 years/30,000 hours

APPLICATIONS

Ideal applications in residential, commercial, retail, and hospitality environments.



PROJECT FIXTURE TYPE DATE






REV 12.20.23

NOMINAL LAMP DATA

DESCRIPTION	MR16 SMART LAMP										
WAITS 4W											
COLOR TEMPERATURE	20K	22K	24K	27K	30K	35K	40K	57K	65K		
LUMENS (Im)	210	223	250	270	284	277	393	322	260 55		
LUMENS PER WATT (Im/w)	47	50	56	60	63	64	79	67			
CRI	94	94	95	96	96	97	93	96	96		
Duv	0.0006	0.0021	0.0031	0.0039	0.0036	0.0021	0.0002	0.0016	0.0013		
Rf	90	92	92	92	92	92	90	92	90		
Rg	101	104	105	105	104	102	99	102	103		
R9	80	85	87	90	91	90	65	90	96		
R13	99	97	99	99	100	98	94	94	90		
R15	94	92	95	97	98	96	91	91	86		
WATTS	4.5	4.5	4.5	4.5	4.5	4.3	5	4.8	4.7		

R1-R15 CRI CHART @ 3000K 97 CRI



PROJECT	FIXTURE TYPE	DATE	







REV 12.20.23

TM-30-15 DATA: The data below is for Pure Smart TruColor™ RGBTW Lamps.

2000K (TruColor™ RGBTW) View Angle: 2 Deg




2200K (TruColor™ RGBTW) View Angle: 2 Deg




0.0020

2400K (TruColor™ RGBTW) View Angle: 2 Deg




2700K (TruColor™ RGBTW)



3000K (TruColor™ RGBTW)


сст 2197К



3500K (TruColor™ RGBTW) View Angle: 2 Deg

4000K (TruColor™ RGBTW) View Angle: 2 Deg


сст 4012К



0.0000

5700K (TruColor™ RGBTW)






6500K (TruColor™ RGBTW)

View Angle: 2 Deg

3539K



PROJECT FIXTURE TYPE DATE

-0.0006