


REVEAL WALL WASH 2

24VDC, PLASTER-IN LED SYSTEM, STATIC WHITE

DESIGNED BY GREGORY KAY | MADE IN AMERICA | PATENT PENDING

REV 03.10.23



DESCRIPTION

Our new generation of the Reveal System washes the wall from the very top of the ceiling highlighting the wall with continuous illumination. Recessed within 5/8" drywall without the need for joist modification. The 24VDC low-voltage system uses PureEdge's superior designer-grade 95+ CRI LEDs rendering art and color in their truest forms while producing uniform brightness. Simply mount the slim profile plaster-in extrusions within 5/8" or thicker drywall, 24" from the projected wall. The system is sold in 1' increments up to 20' and can be cut in the field. Continuing to redefine the relationship between lighting and interior design, Reveal Wall Wash invokes dramatic yet refined illumination by highlighting art and creating depth of architectural features. The Reveal Wall Wash is offered in multiple wattage and color temperatures ranging from 2400K through 4000K. [Click here for all Other Color Temperatures](#). Remote Power Supply is required and ordered separately. Coordinate installation with electrician and drywall contractors. Includes a 5 year pro-rated warranty. For custom quotes, email our design team: design@PureEdgeLighting.com.

DESIGN NOTE

Reveal Wall Wash is an ideal wall washing solution for any space, highlighting art and creating depth within architectural features. Multiple runs of channel mount seamlessly together and may wrap inside corners to wash surrounding walls with uniform controlled illumination up to 95+ CRI.

MAXIMUM LENGTHS BEFORE RE-FEEDING:

5WDC, 4.4 watts per foot - 20'
 7WDC, 7.5 watts per foot - 12'
 10WDC, 9.6 watts per foot - 10'

FINISHES



Satin Aluminum
SA

White
WH

PureEdge is the Original Designer of 5/8" Drywall Lighting Products with the Most Experience in the industry.

System	Watts Per Foot	Length in Feet	Color Temperature	Reflector Finish
RVWW2	5WDC	20FT	ST27K	WH
RVWW2 Reveal Wall Wash	5WDC 4.4 Watts 7WDC 7.5 Watts 10WDC 9.6 Watts	1-20FT 5WDC 1-12FT 7WDC 1-10FT 10WDC	ST24K 2400K Very Warm White ST27K 2700K Incandescent White ST27D 2700K Warm Dim (5WDC only) ST30K 3000K Warm White ST30D 3000K Warm Dim (5WDC only) ST35K 3500K Neutral White ST40K 4000K Cool White	SA Satin Aluminum WH White

LAMPING

- Offered in multiple Static White Color Temperatures: 2400K, 2700K, 3000K, 3500K & 4000K
- Lumen Performance: 575lm/ft at 3000K 10 watts per foot
- Designer Grade High CRI 95+ LEDs
- 5, 7 or 10 watts per foot
- 50,000 Hour Lamp Life
- For additional color temperatures refer to other specifications

REMOTE POWER SUPPLIES*, DIMMERS & CONTROLS (SOLD SEPARATELY)

24VDC, Class 2 wiring

- [Pure Smart™ WiZ Pro Power Supplies & Controls](#)
- [UNI Driver: Universal Dimming \(TRIAC, ELV, 0-10V\)](#)
- [0-10V](#): Requires two dimmers, one for intensity and one for color temperature
- [Lutron Hi-Lume/Ecosystem](#)

*In-Wall Mounting and drop ceiling Kits available for select power supplies

APPLICATIONS

Indoor damp or dry locations only. Reveal Wall Wash is ideal in Residential, Commercial, Retail, and Hospitality Environments.

INCLUDED COMPONENTS

Junction Box, Adjustable Mounting Bars, Reveal Wall Wash Channel(s), Power Feed End Cap, Junction Box Cover, Dead End Cap, Take-Up Box, Drywall Screws, LED Soft Strip, and Lens(es)

COMPLIANCE

ETL, Class 2, Damp Location, Made in USA.

For quick & easy reference, plus the most up-to-date pricing, use our [Reveal Wall Wash Configurator](#).

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

REVEAL WALL WASH 2

24VDC, PLASTER-IN LED SYSTEM, STATIC WHITE

NOMINAL DELIVERED LUMENS

DESCRIPTION	RVWW														
	Wall Wash														
	5w (4.4 watts)					7w (7.5 watts)					10w (9.6 watts)				
WATTS PER FOOT	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K
COLOR TEMPERATURE	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	253	278	303	347	378	413	454	496	568	617	535	588	642	736	800
LUMENS PER WATT (lm/w)	57	63	69	79	85	57	62	68	78	84	56	61	67	76	83
CRI	90+	95+	95+	85+	85+	90+	95+	95+	85+	85+	90+	95+	95+	85+	85+

LENGTH LOAD CHARTS: To determine the necessary wire gauge use our [Voltage Drop Calculator](#).


5 WATTS PER FOOT	
LENGTH IN FEET	WATTS
1	5
2	10
3	16
4	20
5	24
6	29
7	34
8	38
9	43
10	48
11	53
12	58
13	63
14	67
15	72
16	77
17	82
18	87
19	91
20	96

7 WATTS PER FOOT	
LENGTH IN FEET	WATTS
1	8
2	15
3	23
4	30
5	38
6	45
7	53
8	60
9	68
10	75
11	83
12	90

10 WATTS PER FOOT	
LENGTH IN FEET	WATTS
1	10
2	20
3	30
4	40
5	50
6	60
7	70
8	80
9	90
10	100

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

INCLUDED COMPONENTS



A. JUNCTION BOX

Mounts behind drywall with Adjustable Mounting Bars and includes a drywall template for accurate installation. Low Voltage 24VDC wires from Remote Power Supply connect to LED wires inside box. Junction Box opening is concealed with the Reveal Wall Wash Junction Box cover and is required at the beginning of each run.

B. ADJUSTABLE MOUNTING BARS

Provide flexibility for mounting in a variety of spaces.

C. REVEAL WALL WASH CHANNEL

5/8" deep extrusion houses a single row of Commercial and Designer Grade High CRI 95+ LED Strip.

D. POWER FEED END CAP

Provides a connection area for 24VDC wires at beginning of run where LED Strip enters channel.

E. JUNCTION BOX COVER

Conceals Junction Box opening. Required at the beginning of each run.

F. DEAD END CAP PLATE

Provides a finished look and prevents light leak at feed-end of run where LED Strip exits channel.

G. TAKE-UP BOX

Prevents dark spots at end of run by tucking excess LED Strip safely behind wall.

H. DRYWALL SCREWS


Secure channel to drywall and studs/joists.

I. LED STRIP

(Back Side shown) Designer Grade High CRI 95+ LED Strip. See lamp data on for additional details.

J. LENS

0.74" wide diffused lens projects a clean line of light without LED pixelation.




JUNCTION BOX ROUGH-IN COMPONENT

One Junction Box is included with Reveal Wall Wash. Order additional Junction Box separately to rough-in electrical wiring before drywall installation. Quick shipment available.


System	Size	Component
RVWW2	1RE	JBOX
RVWW2 Reveal Wall Wash	1RE 1" Rectangle	JBOX Junction Box

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

INSTALLATION



- A. DIMMER OR SWITCH.**
- B. 120VAC WIRING TO 120V/24VDC REMOTE POWER SUPPLY, FOR IN-WALL MOUNTING KIT.**
- C. IN-WALL MOUNTING KIT.**
- D. 24VDC, CLASS 2 WIRING.**
- E. REVEAL WALL WASH SYSTEM.**




■ Direction of Light


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------

REVEAL WALL WASH 2


24VDC, PLASTER-IN LED SYSTEM, STATIC WHITE




DIRECTION OF LIGHT



CANDLE POWER DISTRIBUTION



WALL WASH DIRECTION OF LIGHT SHOWN WITH 10 WATT, 3000K VERSION



FIXTURE MOUNTED 24" FROM WALL
7W 30K CHANNEL AND DIFFUSED LENS

	1'	2.5'	4'	5.5'	7'
1"	50	50	53	53	43
3"	90	90	104	97	81
6"	113	136	140	137	116
1'	122	138	140	137	113
18"	115	128	128	120	100
2'	100	113	113	109	86
3'	76	89	90	83	67
4'	62	72	70	68	56
5'	50	58	59	55	46
6'	41	46	47	44	38
7'	34	37	38	35	31
8'	27	30	30	30	26
9'	23	25	25	25	21
10'	20	22	22	22	20
11'	16	18	18	18	16
12'	13	15	15	15	13
13'	10	12	12	12	10

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


TM30 DATA

24VDC, PLASTER-IN LED SYSTEM, STATIC WHITE & WARM DIM

TM-30-15 DATA: The data below is for bare LED Static White Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

2400K | Rf: 84.5 | Rg: 94.4

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%

2700K | Rf: 87.7 | Rg: 96.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	8.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.8%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%

3000K | Rf: 88.1 | Rg: 99.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%

3500K | Rf: 86.1 | Rg: 95.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.8	-3.8%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.6	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	96.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.8%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

4000K | Rf: 87.6 | Rg: 96.8

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.8	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-6.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.8%
10	78.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	88.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------