


DESIGNED BY GREGORY KAY I ASSEMBLED IN AMERICA REV 01.18.22





DESCRIPTION

LEDs are field replaceable. Fixture is Non-IC rated. Suitable for new residential, new commercial, and remodel. Lights textured walls up to 30' high. Mounts flush to ceilings or recessed within a pocket cove for the most dramatic effect. Link multiple Stratus fixtures to create long runs. Includes one internal LED Power Supply per unit. (0-10V for WW and CW; DMX for RGB). Feed fixture with 120-277VAC. Coordinate installation with electrician and drywall contractors.

APPLICATIONS

Indoor or Outdoor under Awning. Wall Grazer, General Lighting, and Retail applications

LAMP

Lumen values are based on the Warm White 3000K test.

VERSION	WATTS PER FOOT	LUMENS PER FOOT		90+CRI	RGB
3000K WARM WHITE	15WDC	56	670	•	
4200K COOL WHITE	15WDC	67	804	•	
RED, GREEN, AND BLUE	15WDC	N/A	N/A		•

INCLUDED COMPONENTS

Wall Mounting Bracket, Housing, Joiner Bracket, Reflector, LED Panel, Power Supply, and Louver


DIMMING & CONTROLS

Dimmable Power Supply included (0-10V) for WW and CW; (DMX) for RGB. Controllers sold separately


ACCESSORIES

End Caps

INDOOR 120V-277V STANDARD POWER SUPPLY



OUTDOOR UNDER AWNING 120V-277V STANDARD POWER SUPPLY




PROJECT	FIXTURE TYPE	DATE	
FROJECT	IIXIONL I IFL	DAIL	



PURE LIGHTING

DESIGNED BY GREGORY KAY I ASSEMBLED IN AMERICA REV 01.18.22

INCLUDED COMPONENTS



A. WALL MOUNTING BRACKET

For all three types of installation conditions: new residential, new commercial, and remodel.

B. 4' HOUSING

Non-IC, 0.08" thick die-formed aluminum.

C. 1' HOUSING

Non-IC, 0.08" thick die-formed aluminum.

D. JOINER BRACKET

Joins multiple lengths of Stratus fixture.

E. 4' REFLECTOR

Precision-cut aluminum.

F. 1' REFLECTOR

Precision-cut aluminum.

G. 4' LED PANEL

Integrated 3000K, 42000K, or RGB LEDs.


H. 1' LED PANEL

Integrated 3000K, 42000K, or RGB LEDs.

I. END CAP

Sold in pairs. Required at end of run.





END CAP

Sold in pairs. Required at end of run.



PROJECT	FIXTURE TYPE	DATE	



PURE LIGHTING

DESIGNED BY GREGORY KAY | ASSEMBLED IN AMERICA

REV 01.18.22

