


TRULINE TRIM 1.6A STATIC WHITE

24VDC LED SYSTEM, 1/2" TRIM

DESIGNED BY GREGORY KAY | ASSEMBLED IN AMERICA

REV 06.08.26



DESCRIPTION

TruLine Trim 1.6A is a recessed 24VDC LED system that features a paintable 1/2" trim. The slim channel extrusions recess within any flat surface, including 5/8" drywall, tile, and millwork, eliminating the need for stud or joist modification. The channel, LED strips, and lenses are field-cuttable and ordered in 1' increments (up to 40' before re-feeding), providing flexibility and unparalleled ease of installation. TruLine Trim 1.6A is offered in a broad range of wattages and color temperatures up to 95+ CRI, ranging from **2400K** through **4000K**. Click here for all [Other Color Temperatures](#). 24VDC Remote Power Supplies are required and sold separately. Coordinate installation with electrical and drywall contractors. Includes a 5-year pro-rated warranty. For custom designs and quotes, email your drawings to design@PureEdgeLighting.com.

DESIGN NOTE

TruLine Trim 1.6A can be installed on a single surface, join runs on multiple planes from wall to ceiling, or from one wall to an adjacent wall. Use TruLine Trim 1.6A Do-It-Yourself (**DIY**) with pre-formed components to create desired configurations, including Mitered Picture Frame and Outside or Inside Corners for Room Wrapping installations.

ORDERING & INSTALLATION

TruLine Trim 1.6A may be secured to studs spaced 13"-24" apart or between studs with provided mounting straps. Order in 1' increments, field-cuttable to any length.

LAMP

- Offered in multiple Static White Color Temperatures: 2400K, 2700K, 3000K, 3500K & 4000K
- Lumen Performance: 2235lm/ft at 3000K 14W per foot with the
- High Output strip
- Designer Grade High CRI 94+ LEDs
- Average life: 50,000 hours
- For additional color temperatures refer to other specifications

MAXIMUM LENGTHS BEFORE RE-FEEDING:

- 5 watts per foot - 40' (2 x 2.5WDC)
- 10 watts per foot - 20' (2 x 5WDC)
- 14 watts per foot - 12' (2 x 7.5WDC)

REMOTE POWER SUPPLIES*, DIMMERS & CONTROLS (SOLD SEPARATELY)

24VDC, Class 2 wiring

- [Pure Smart™ WiZ Pro Power Supplies & Controls](#)
- [UNI Driver: Universal Dimming \(TRIAC, ELV, 0-10V\)](#)

MAKE IT SMART

- [Pure Smart™ WiZ Pro Controls](#)
- [2-in-1 Power Driver and Dimmer](#)

*In-Wall Mounting and drop ceiling Kits available for select power supplies

APPLICATIONS

Designed for any indoor space with drywall. Ideal applications in Residential, Commercial, Retail, and Hospitality environments


COMPLIANCE

ETL, Class 2, Indoor Damp Location, Assembled in the USA


PureEdge is the Original Designer of 5/8" Drywall Lighting Products with the Most Experience in the industry.

System	Watts Per Foot	Length in Feet	Color Temperature	Finish
TTL1.6A	5WDC	40FT	ST27K	WH
TTL1.6A TruLine Trim 1.6A	5WDC 2x2.5 Watts (40 ft Max) 10WDC 2x5 Watts (20 ft Max) 14WDC 2x7.5 Watts (12 ft Max)	1-40FT (5W) 1-20FT (10W) 1-12FT (14W)	ST24K 2400K Very Warm White ST27K 2700K Incandescent White ST30K 3000K Warm White ST35K 3500K Neutral White ST40K 4000K Cool White 27KH 2700K Incandescent White High Output 30KH 3000K Warm White High Output 35KH 3500K Neutral White High Output 40KH 4000K Cool White High Output	BK Black WH White RAL 9010

TRULINE TRIM 1.6A STATIC WHITE 24VDC LED SYSTEM, 1/2" TRIM



INCLUDED COMPONENTS, TRADITIONAL DIMMING



A. JUNCTION BOX

Mounts behind drywall with Adjustable Mounting Bars. Low Voltage 24VDC wires from Remote Power Supply connect to LED wires inside box. Junction Box opening is covered by the channel, and required at the beginning of each run.

B. ADJUSTABLE MOUNTING BARS

Provide flexibility for mounting in a variety of spaces and orientations. May be secured to studs that are spaced 13"-24" apart.

C. TRULINE TRIM 1.6A CHANNEL

5/8" deep extrusion house for two rows of LED Strips.

D. POWER END CAP

Provides a finished look and prevents light leak at feed-end of runs where LED Strip enters the channel.

E. TAKE-UP BOX

Prevents dark spots at the end of a run by tucking excess LED Strip safely behind wall.

F. TOGGLE BOLT AND SCREW


Secures channel to drywall and stud.

G. LED STRIPS

Your selection of LED Strip CCT. TruLine Trim 1.6A comes with two LED Strips.

H. LENS

1.6" wide diffused white lens projects a clean line of light without pixelation.



JUNCTION BOX ROUGH-IN COMPONENT

One Junction Box is included with TruLine 1.6A. Order additional Junction Box separately to rough-in electrical wiring before drywall installation. Quick shipment available.

System	Size	Component
TL1.6A	1RE	JBOX
TL1.6A TruLine 1.6A	1RE 1" Rectangle	JBOX Junction Box

TRULINE TRIM 1.6A STATIC WHITE

24VDC LED SYSTEM, 1/2" TRIM

REV 06.08.26

NOMINAL DELIVERED LUMENS

	STATIC WHITE														
WATTS PER FOOT	5W (2x2.5 Watts)					10W (2x4.4 Watts)					14W (2x7.5 Watts)				
COLOR TEMPERATURE	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	456	461	480	551	581	843	852	887	1018	1073	1301	1315	1370	1572	1572
LUMENS PER WATT (lm/w)	91	92	96	110	116	96	97	101	116	122	89	90	94	108	108
CRI	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+	92+

	STATIC WHITE HIGH OUTPUT											
WATTS PER FOOT	5W (2x2.5 Watts)				10W (2x4.4 Watts)				14W (2x7.5 Watts)			
COLOR TEMPERATURE	27K	30K	35K	40K	27K	30K	35K	40K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	790	814	837	803	1611	1629	1770	1661	2155	2235	2408	2297
LUMENS PER WATT (lm/w)	275	287	298	294	265	274	293	285	259	266	289	281
CRI	95	94	93	93	95	94	93	93	95	94	93	93

LENGTH LOAD CHARTS: To determine the necessary wire gauge use our [Voltage Drop Calculator](#).

5 WATTS PER FOOT (2 X 2.5W)			
LENGTH IN FEET	WATTS	LENGTH IN FEET	WATTS
1	5	21	102
2	10	22	106
3	14	23	110
4	19	24	116
5	24	25	120
6	29	26	124
7	34	27	130
8	38	28	134
9	43	29	140
10	48	30	144
11	53	31	148
12	58	32	154
13	63	33	158
14	67	34	164
15	72	35	168
16	77	36	172
17	82	37	178
18	87	38	182
19	91	39	188
20	96	40	192

10 WATTS PER FOOT (2 X 4.4W)	
LENGTH IN FEET	WATTS
1	10
2	19
3	29
4	38
5	48
6	58
7	67
8	77
9	86
10	96
11	106
12	116
13	124
14	134
15	144
16	154
17	164
18	174
19	182
20	192


14 WATTS PER FOOT (2 X 7.5W)	
LENGTH IN FEET	WATTS
1	14
2	28
3	42
4	56
5	70
6	84
7	98
8	112
9	126
10	140
11	154
12	168

LED STRIP TM30 DATA

24VDC, LED SYSTEM

TM-30-15 DATA: The data below is for bare LED Static White Strip. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.


2400K | Rf: 84.5 | Rg: 94.4
Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	92	-2.4%	1.5%
2	94.7	-2.1%	-0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%


2700K | Rf: 87.7 | Rg: 96.1
Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	88.0	-4.3%	2.6%
2	91.6	-2.4%	2.0%
3	93.7	-1.4%	1.9%
4	88.9	-5.6%	-3.1%
5	92.3	-5.5%	-0.5%
6	92.9	-3.5%	0.1%
7	84.5	-7.5%	4.6%
8	90.8	-3.0%	4.4%
9	84.5	-1.3%	8.3%
10	83.9	2.0%	9.8%
11	87.2	5.3%	7.1%
12	89.2	5.4%	-2.6%
13	88.7	0.3%	-7.8%
14	86.8	1.7%	-9.3%
15	87.6	-5.4%	-1.3%
16	83.6	-3.3%	-9.5%


3000K | Rf: 88.1 | Rg: 99.7
Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	92.5	-3.1%	0.3%
2	93.3	-2.3%	1.9%
3	90.9	-0.8%	3.9%
4	94.3	-1.1%	1.4%
5	92.5	-2.6%	1.5%
6	96.4	1.2%	-0.3%
7	92.6	-2.5%	-0.0%
8	96.9	-1.4%	0.2%
9	92.3	-1.8%	4.3%
10	86.6	-0.7%	7.0%
11	86.5	2.4%	8.2%
12	89.8	5.9%	1.7%
13	93.9	2.6%	-2.7%
14	89.4	5.1%	-5.8%
15	90.1	-0.1%	-4.7%
16	86.5	0.3%	-9.7%


3500K | Rf: 86.1 | Rg: 95.5
Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	90.8	-3.8%	0.3%
2	92.3	-2.8%	2.1%
3	89.7	-1.0%	4.3%
4	92.6	-1.4%	1.7%
5	91.8	-3.1%	1.3%
6	96.2	0.8%	-0.4%
7	92.9	-3.2%	0.2%
8	94.3	-2.5%	1.5%
9	90.4	-2.5%	5.2%
10	84.3	-1.4%	9.5%
11	83.1	3.5%	9.8%
12	88.2	4.8%	3.4%
13	94.0	2.7%	-2.0%
14	88.7	5.9%	-5.8%
15	88.7	0.7%	-5.9%
16	86.8	-0.7%	-6.7%

4000K | Rf: 87.6 | Rg: 96.8
Color Vector Graphic



■ Test ■ Reference

		GRAPHIC SHIFTS %	
HUE BIN	Rf	CHROMA	HUE
1	88.9	-2.4%	2.5%
2	93.3	-0.4%	0.8%
3	94.8	-1.0%	-0.6%
4	87.9	-4.9%	-3.6%
5	85.3	-9.4%	-2.6%
6	90.2	-6.0%	0.2%
7	85.3	-7.6%	4.6%
8	83.7	-4.1%	8.2%
9	79.5	-1.1%	13.8%
10	78.6	1.5%	12.1%
11	83.5	6.4%	7.8%
12	90.9	3.6%	-1.1%
13	88.3	1.7%	-6.3%
14	91.9	-0.4%	-2.2%
15	84.5	-0.9%	-5.5%
16	84.7	-1.1%	-4.4%