



Five (5) Zipp Waves are shown here


DESCRIPTION

Add curves and volume to any space with the Zipp Wave Suspension Downlight. This contemporary, curvy, linear LED fixture offers lighting that is crisp and spot-free. It is available in a range of increments from 48" to 240" (20'), a 100° beam spread, optional adjustable white or black louver, multiple finishes, and a spectrum of color temperatures including Warm Dim. Fixture includes a 5-year pro-rated warranty. For custom designs and quotes, send drawings to design@PureEdgeLighting.com.

INSTALLATION

- Mounts to a standard junction box, pre-wired from either a 120V with a 60 watt NON-IC (50W-IC) power supply that fits in the ceiling electrical junction box, or from a remote power supply feeding 24VDC up to 100 watts at a maximum of 40' away
- Includes your choice of one or two canopies: one for remote power (under 60 watts NON-IC, fits in Jbox), one blank at end cap - 2R2, 2S2, 4R2, 4S2
- Includes adjustable 12' coaxial and aircraft cables (additional aircraft cables included for support when fixture exceeds 96")
- Power supplies sold separately

FINISHES



Satin Black **BK** Chrome **CH** Satin Nickel **SN** White **WH**

LENSES

- Available in a 100° white diffused lens
- Optional Black or White louver available

LAMPING

- Multiple color temperatures from 2400K-4000K including Warm Dim
- Warm Dim: 2700K to 2000K (**27D**) or 3000K to 2000K (**30D**)
- 50,000 Hour Lamp Life

REMOTE POWER SUPPLIES* & DIMMERS (SOLD SEPARATELY)

24VDC, Class 2 wiring

Static White & Warm Dim

- [UNI Driver: Universal Dimming \(TRIAC, ELV, 0-10V\)](#)
- [Electronic Low Voltage \(ELV\)](#)† 50W IC or 60W Non-IC (fits inside junction box)


Lutron

- [Lutron](#) Hi-Lume/Ecosystem

*In-Wall Mounting and drop ceiling kits available for select power supplies

APPLICATIONS


Designed for indoor use only. Ideal application environments include: restaurants, hallways, conference rooms, kitchens, dining rooms, architectural lighting, general lighting, and retail




System	Wattage Per Foot	Canopy	Nominal Size (Inches)	Color Temperature	Finish
WSD	5W 5 Watt	2R 2.8" Round Canopy	240	22K	SN
WSDW Zipp Wave Suspension Diffused Lens with White Louver	7W 7.5 Watt	2S 2.8" Square Canopy	48-240 Order in various increments from 48" to 240" at 5 watts per foot. Maximum shipping length for Chrome is 84"	24K 2400K Very Warm White	BK Satin Black
WSDB Zipp Wave Suspension Diffused Lens with Black Louver		4R 4.6" Round Canopy		27K 2700K Incandescent White	CH Chrome
		4S 4.6" Square Canopy		27D 2700K Warm Dim (5W only)	SN Satin Nickel
		2R2 2x2.8" Round Canopies		30K 3000K Warm White	WH White
		2S2 2x2.8" Square Canopies		30D 3000K Warm Dim (5W only)	
		4R2 2x4.6" Round Canopies		35K 3500K Neutral White	
		4S2 2x4.6" Square Canopies		40K 4000K Cool White	

*See length chart on pg 2 for exact dimensions


PROJECT	FIXTURE TYPE	DATE
---------	--------------	------



DIFFUSED WHITE LENS



DIFFUSED WHITE LENS WITH WHITE LOUVER



CLEAR FROSTED LENS WITH BLACK LOUVER

Lamp Data: Lamp data for Zipp Wave Suspension Downlight with Remote - End Feed

WSD												
DESCRIPTION	100 Degree Diffused White Lens without Lens											
WATTS PER FOOT	5W (4.4 watts)						7W (7.5 watts)					
COLOR TEMPERATURE	24K	27K	27D*	30K	30D*	35K	40K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	232	255	260	278	284	319	346	381	418	457	523	569
LUMENS PER WATT (lm/w)	53	58	54	63	59	72	79	52	57	63	72	78
CRI	90+	95+	95+	95+	95+	85+	84	90+	95+	95+	85+	84

*27D & 30D use 7.5 watts per foot.


WSDW												
DESCRIPTION	100 Degree Diffused White Lens with White Louver											
WATTS PER FOOT	5W (4.4 watts)						7W (7.5 watts)					
COLOR TEMPERATURE	24K	27K	27D*	30K	30D*	35K	40K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	145	159	162	174	177	199	216	237	261	285	327	355
LUMENS PER WATT (lm/w)	33	36	34	39	37	45	49	33	36	39	45	49
CRI	90+	95+	95+	95+	95+	85+	84	90+	95+	95+	85+	84

*27D & 30D use 7.5 watts per foot.

WSDB												
DESCRIPTION	100 Degree Diffused White Lens with Black Louver											
WATTS PER FOOT	5W (4.4 watts)						7W (7.5 watts)					
COLOR TEMPERATURE	24K	27K	27D*	30K	30D*	35K	40K	24K	27K	30K	35K	40K
LUMENS PER FOOT (lm/ft)	90	99	101	108	110	124	134	148	162	177	203	221
LUMENS PER WATT (lm/w)	20	22	21	25	23	28	31	20	22	24	28	30
CRI	90+	95+	95+	95+	95+	85+	84	90+	95+	95+	85+	84

*27D & 30D use 7.5 watts per foot.

5W DIFFUSED WHITE			
Distance	Foot Candles 5W	Beam Width Vert. Spread 101.1°	Beam Width Horiz. Spread 97.4°
1.7ft	120fc	4.1ft	3.9ft
3.3ft	39fc	8.0ft	7.5ft
5.0ft	16fc	12.1ft	11.4ft
6.7ft	10fc	16.3ft	15.3ft
8.3ft	6fc	20.2ft	18.9ft
10.0ft	4fc	24.3ft	22.8ft



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--



ZIPP WAVE

LED SUSPENSION DOWNLIGHT WITH REMOTE POWER - END FEED



REV 02.23.22

Length Chart: Actual lengths for Zipp Suspension Downlight - Remote Power Supply

STATIC WHITE									
Ordering Code (Nominal Size)	Actual Length (Inches)	5W (5 Watts)	Power Supply	7W (7.5 Watts)	Power Supply	Ordering Code (Nominal Size)	Actual Length (Inches)	5W (5 Watts)	Power Supply
48	48.6	20	PSB-40W-UNI-24VDC	30	PSB-40W-UNI-24VDC	202	201.4	84	PSB-96W-UNI-24VDC
51	51.0	21	PSB-40W-UNI-24VDC	32	PSB-40W-UNI-24VDC	204	203.8	85	PSB-96W-UNI-24VDC
53	53.4	22	PSB-40W-UNI-24VDC	33	PSB-40W-UNI-24VDC	207	206.2	86	PSB-96W-UNI-24VDC
56	55.8	23	PSB-40W-UNI-24VDC	35	PSB-40W-UNI-24VDC	209	208.6	87	PSB-96W-UNI-24VDC
58	58.1	24	PSB-40W-UNI-24VDC	36	PSB-40W-UNI-24VDC	212	210.9	88	PSB-96W-UNI-24VDC
60	60.5	25	PSB-40W-UNI-24VDC	38	PSB-40W-UNI-24VDC	214	213.3	89	PSB-96W-UNI-24VDC
63	62.9	26	PSB-40W-UNI-24VDC	39	PSB-40W-UNI-24VDC	216	215.7	90	PSB-96W-UNI-24VDC
65	65.3	27	PSB-40W-UNI-24VDC	41	PSB-60W-UNI-24VDC	219	218.1	91	PSB-96W-UNI-24VDC
68	67.7	28	PSB-40W-UNI-24VDC	43	PSB-60W-UNI-24VDC	221	220.5	92	PSB-96W-UNI-24VDC
70	70.1	29	PSB-40W-UNI-24VDC	44	PSB-60W-UNI-24VDC	224	222.9	93	PSB-96W-UNI-24VDC
72	72.5	30	PSB-40W-UNI-24VDC	45	PSB-60W-UNI-24VDC	226	225.3	94	PSB-96W-UNI-24VDC
75	74.9	31	PSB-40W-UNI-24VDC	47	PSB-60W-UNI-24VDC	228	227.7	95	PSB-96W-UNI-24VDC
77	77.2	32	PSB-40W-UNI-24VDC	48	PSB-60W-UNI-24VDC	231	230.0	96	PSB-96W-UNI-24VDC
80	79.6	33	PSB-40W-UNI-24VDC	50	PSB-60W-UNI-24VDC	233	232.4	97	PSB-100W-ELV-24VDC
82	82.0	34	PSB-40W-UNI-24VDC	51	PSB-60W-UNI-24VDC	236	234.8	98	PSB-100W-ELV-24VDC
84*	84.4	35	PSB-40W-UNI-24VDC	53	PSB-60W-UNI-24VDC	238	237.2	99	PSB-100W-ELV-24VDC
87	86.8	36	PSB-40W-UNI-24VDC	54	PSB-60W-UNI-24VDC	240	239.6	100	PSB-100W-ELV-24VDC
89	89.2	37	PSB-40W-UNI-24VDC	56	PSB-60W-UNI-24VDC				
92	91.6	38	PSB-40W-UNI-24VDC	58	PSB-60W-UNI-24VDC				
94	94.0	39	PSB-40W-UNI-24VDC	59	PSB-60W-UNI-24VDC				
96	96.4	40	PSB-60W-UNI-24VDC	60	PSB-96W-UNI-24VDC				
99	98.7	41	PSB-60W-UNI-24VDC	62	PSB-96W-UNI-24VDC				
101	101.1	42	PSB-60W-UNI-24VDC	63	PSB-96W-UNI-24VDC				
104	103.5	43	PSB-60W-UNI-24VDC	65	PSB-96W-UNI-24VDC				
106	105.9	44	PSB-60W-UNI-24VDC	66	PSB-96W-UNI-24VDC				
108	108.3	45	PSB-60W-UNI-24VDC	68	PSB-96W-UNI-24VDC				
111	110.7	46	PSB-60W-UNI-24VDC	69	PSB-96W-UNI-24VDC				
113	113.1	47	PSB-60W-UNI-24VDC	71	PSB-96W-UNI-24VDC				
116	115.4	48	PSB-60W-UNI-24VDC	73	PSB-96W-UNI-24VDC				
118	117.8	49	PSB-60W-UNI-24VDC	74	PSB-96W-UNI-24VDC				
120**	120.2	50	PSB-60W-UNI-24VDC	75	PSB-96W-UNI-24VDC				
123	122.6	51	PSB-60W-UNI-24VDC	77	PSB-96W-UNI-24VDC				
125	125.0	52	PSB-60W-UNI-24VDC	78	PSB-96W-UNI-24VDC				
128	127.4	53	PSB-60W-UNI-24VDC	80	PSB-96W-UNI-24VDC				
130	129.8	54	PSB-60W-UNI-24VDC	81	PSB-96W-UNI-24VDC				
132	132.2	55	PSB-60W-UNI-24VDC	83	PSB-96W-UNI-24VDC				
135	134.5	56	PSB-60W-UNI-24VDC	84	PSB-96W-UNI-24VDC				
137	136.9	57	PSB-60W-UNI-24VDC	86	PSB-96W-UNI-24VDC				
140	139.3	58	PSB-60W-UNI-24VDC	87	PSB-96W-UNI-24VDC				
142	141.7	59	PSB-60W-UNI-24VDC	89	PSB-96W-UNI-24VDC				
144	144.1	60	PSB-96W-UNI-24VDC	90	PSB-96W-UNI-24VDC				
147	146.5	61	PSB-96W-UNI-24VDC	92	PSB-96W-UNI-24VDC				
149	148.9	62	PSB-96W-UNI-24VDC	93	PSB-96W-UNI-24VDC				
152	151.3	63	PSB-96W-UNI-24VDC	95	PSB-96W-UNI-24VDC				
154	153.6	64	PSB-96W-UNI-24VDC	96	PSB-96W-UNI-24VDC				
156	156.0	65	PSB-96W-UNI-24VDC	98	PSB-100W-ELV-24VDC				
159	158.4	66	PSB-96W-UNI-24VDC	99	PSB-100W-ELV-24VDC				
161	160.8	67	PSB-96W-UNI-24VDC						
164	163.2	68	PSB-96W-UNI-24VDC						
166	165.6	69	PSB-96W-UNI-24VDC						
168	168.0	70	PSB-96W-UNI-24VDC						
171	170.4	71	PSB-96W-UNI-24VDC						
173	172.7	72	PSB-96W-UNI-24VDC						
176	175.1	73	PSB-96W-UNI-24VDC						
178	177.5	74	PSB-96W-UNI-24VDC						
180	179.9	75	PSB-96W-UNI-24VDC						
183	182.3	76	PSB-96W-UNI-24VDC						
185	184.7	77	PSB-96W-UNI-24VDC						
188	187.1	78	PSB-96W-UNI-24VDC						
190	189.5	79	PSB-96W-UNI-24VDC						
192	191.8	80	PSB-96W-UNI-24VDC						
195	194.2	81	PSB-96W-UNI-24VDC						
197	196.6	82	PSB-96W-UNI-24VDC						
200	199.0	83	PSB-96W-UNI-24VDC						

*Maximum Chrome Shipping Length **Max Shipping Length

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--



ZIPP WAVE

LED SUSPENSION DOWNLIGHT WITH REMOTE POWER - END FEED



REV 02.23.22

Length Chart: Actual lengths for Zipp Suspension Downlight - Remote Power Supply

27D & 30D (WARM DIM)							
Ordering Code (Nominal Size)	Actual Length (Inches)	5W (5 Watts)	Power Supply	Ordering Code (Nominal Size)	Actual Length (Inches)	5W (5 Watts)	Power Supply
48		20	PSB-40W-UNI-24VDC	147		61	PSB-96W-UNI-24VDC
51		21	PSB-40W-UNI-24VDC	150		63	PSB-96W-UNI-24VDC
54		23	PSB-40W-UNI-24VDC	153		64	PSB-96W-UNI-24VDC
57		24	PSB-40W-UNI-24VDC	156		65	PSB-96W-UNI-24VDC
60		25	PSB-40W-UNI-24VDC	159		66	PSB-96W-UNI-24VDC
63		26	PSB-40W-UNI-24VDC	162		68	PSB-96W-UNI-24VDC
66		28	PSB-40W-UNI-24VDC	165		69	PSB-96W-UNI-24VDC
69		29	PSB-40W-UNI-24VDC	168		70	PSB-96W-UNI-24VDC
72		30	PSB-40W-UNI-24VDC	171		71	PSB-96W-UNI-24VDC
75		31	PSB-40W-UNI-24VDC	174		73	PSB-96W-UNI-24VDC
78		33	PSB-40W-UNI-24VDC	177		74	PSB-96W-UNI-24VDC
81		34	PSB-40W-UNI-24VDC	180		75	PSB-96W-UNI-24VDC
84*		35	PSB-40W-UNI-24VDC	183		76	PSB-96W-UNI-24VDC
87		36	PSB-40W-UNI-24VDC	186		78	PSB-96W-UNI-24VDC
90		38	PSB-40W-UNI-24VDC	189		79	PSB-96W-UNI-24VDC
93		39	PSB-40W-UNI-24VDC	192		80	PSB-96W-UNI-24VDC
96		40	PSB-60W-UNI-24VDC	195		81	PSB-96W-UNI-24VDC
99		41	PSB-60W-UNI-24VDC	198		83	PSB-96W-UNI-24VDC
102		43	PSB-60W-UNI-24VDC	201		84	PSB-96W-UNI-24VDC
105		44	PSB-60W-UNI-24VDC	204		85	PSB-96W-UNI-24VDC
108		45	PSB-60W-UNI-24VDC	207		86	PSB-96W-UNI-24VDC
111		46	PSB-60W-UNI-24VDC	210		88	PSB-96W-UNI-24VDC
114		48	PSB-60W-UNI-24VDC	213		89	PSB-96W-UNI-24VDC
117		49	PSB-60W-UNI-24VDC	216		90	PSB-96W-UNI-24VDC
120**		50	PSB-60W-UNI-24VDC	219		91	PSB-96W-UNI-24VDC
123		51	PSB-60W-UNI-24VDC	222		93	PSB-96W-UNI-24VDC
126		53	PSB-60W-UNI-24VDC	225		94	PSB-96W-UNI-24VDC
129		54	PSB-60W-UNI-24VDC	228		95	PSB-96W-UNI-24VDC
132		55	PSB-60W-UNI-24VDC	231		96	PSB-96W-UNI-24VDC
135		56	PSB-60W-UNI-24VDC	234		98	PSB-100W-ELV-24VDC
138		58	PSB-60W-UNI-24VDC	237		99	PSB-100W-ELV-24VDC
141		59	PSB-60W-UNI-24VDC	240		100	PSB-100W-ELV-24VDC
144		60	PSB-96W-UNI-24VDC				


*Maximum Chrome Shipping Length **Max Shipping Length

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

COMPONENTS Swag Bar & Hook, Swag Hook, and T-Bar are compatible with all Power Canopy options and may be required based on lighting design and application


NEW CONSTRUCTION & REMODEL 2" COVER FOR 4" SQUARE JUNCTION BOX

The New Construction NC2-JBOX Cover is included with the 2" Round and Square Canopies and is not required for the 4" Square Canopies. NC2 New Construction Junction Box Cover mounts to a standard 4" Electrical Box or Octagon Box, converting it to a 2" Plaster Ring for use with the 2R (Round) or 2S (Square) Canopy. The Remodel RM2-JBOX Plaster Plate cover is used with an existing 4" Square Junction Box and standard Round Plaster Ring. The PS-60L-ELV-24VDC (50 Watt IC, 60 Watt Non-IC) will fit inside the NC2 or RM2-JBOX Cover and Electrical Junction Box for a flush look.




CIRRUS REMOTE POWER CANOPIES (INCLUDED)

Canopies are included with Canopy ordering code. The 2" Round and Square Canopy includes a special Plaster Ring NC2-JBOX (above). The 4" Square or Round Canopy fits on a standard 4" Electrical Box with Round Plaster Ring and the PS-60L-ELV-24VDC 50 Watt IC, 60 Watt Non-IC) will fit inside the NC2 or RM2-JBOX Cover and Electrical Junction Box for a flush look. Vanishing Point Plaster in system with No Canopy, only see cable going through drywall ceiling with GJ24.




2 inch or 4 inch Canopy (Not Included)






CHANNEL SUSPENSION ADJUSTABLE SWAG BAR AND HOOK

Channel Suspension Adjustable Swag Bar and Hook allows a cable to form a straight connection to the channel when the Power Canopy is not located directly above the fixture. Use when you have two or more canopies (power supplies) on the same fixture run. The Adjustable Swag Hook is compatible with the 2R, 2S, 4R and 4S Power Canopies (Canopy not included).




CHANNEL SUSPENSION SWAG HOOK

The clear plastic Swag Hook extends a cable from an electrical box that is not located directly above desired fixture location.











CHANNEL SUSPENSION ADJUSTABLE T-BAR CLIP

Channel Suspension Adjustable T-Bar Clip mounts to T-Bar grid ceilings. Available in Satin Nickel Hardware as Adjustable Power and Non-Power versions.



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


Drawings: Drawings are shown with 2" round canopy, 2" square canopy, 4" round canopy, and 4" square canopy




PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

Drawings: Side-view shown with 2" or 4" canopy

Zipp Wave Suspension Downlight with Remote Power 4" Canopy Shown with Louver




Zipp Wave Suspension Downlight with Remote Power 2" Canopy Shown with Louver




PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--

Drawings: Side-view shown with two 2 and 4 inch canopies; one for remote power, one blank

Zipp Wave Suspension Downlight with Remote Power 4" Canopies Shown with Louver




Zipp Wave Suspension Downlight with Remote Power 2" Canopies Shown with Louver



PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--


Wiring Diagram: Wiring diagram for Static White with ELV Dimmer

- Application:** ELV dimming for Zipp Wave Suspension Downlight with Remote Power, End Feed Canopy, Static White
- Power Supply:** Class 2, 24VDC output: 120VAC input, PS-60L-ELV-24VDC (Fits in Jbox)
- Remote Power Supplies:** PSB-60W-ELV-24VDC, PSB-100W-ELV-24VDC, UL 2108; PSB-200W-ELV-24VDC
- Dimming:** Dimmable with ELV dimmer: Legrand, Adorne ADTP703TU; Lutron: Diva DVELV-300P, Skylark SELVz-300P, Maestro MAELV-600 and Radio Ra 2



Wiring Diagram: Wiring diagram for Static White with 0-10 Volt Dimmer

- Application:** 0-10V dimming for Zipp Wave Suspension Downlight with Remote Power, End Feed Canopy, Static White
- Remote Power Supplies:** UL Class 2, 24VDC output: 120/277 VAC input, PSB-60W-010-24VDC, PSB-100W-010-24VDC, UL 2108; PSB-200W-010-24VDC
- Dimming:** Dimmable with 0-10 dimmer: Philips: Sunrise SR1200ZTUNV; Lutron: Diva DDTV-WH, Nova-T NTSTV-DV-XX, Graftix Eye QS QSGRJ-XP, Radio RA2 RRD-1-ND; Leviton: LEV40050, IP710-LFZ; Legrand ADPD4FBL3P2W4



PROJECT	FIXTURE TYPE	DATE
---------	--------------	------


TM30 DATA

LED SUSPENSION DOWNLIGHT WITH REMOTE POWER - END FEED

TM-30-15 DATA: The data below is for SS2C, SS5C, SS7C, and SS10C bare LED Soft Strips. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

2400K | Rf: 91.2 | Rg: 96.8

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	92.0	-2.4%	1.5%
2	94.7	-2.1%	0.0%
3	95.4	-1.9%	-0.1%
4	88.7	-6.7%	-3.1%
5	92.8	-5.6%	1.0%
6	92.7	-3.4%	3.4%
7	89.9	-4.3%	4.1%
8	92.4	-1.4%	4.4%
9	89.0	-0.6%	5.8%
10	88.9	0.4%	6.2%
11	89.7	4.0%	5.4%
12	92.6	3.0%	-0.7%
13	90.9	1.1%	-7.0%
14	89.9	0.5%	-5.8%
15	92.1	-3.2%	0.1%
16	88.9	-1.7%	-6.3%

2700K | Rf: 87.7 | Rg: 96.1

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	86.4	-5.6%	2.3%
2	89.7	-3.3%	3.1%
3	90.5	-1.5%	3.8%
4	90.0	-4.3%	1.1%
5	92.9	-3.7%	0.2%
6	93.5	-2.5%	-0.8%
7	86.3	-7.2%	2.5%
8	90.7	-4.0%	3.2%
9	85.2	-2.4%	8.1%
10	81.7	0.9%	10.8%
11	85.4	4.5%	8.9%
12	88.7	5.7%	-1.4%
13	88.3	1.3%	-7.9%
14	85.1	2.4%	-10.4%
15	88.1	-4.8%	-2.7%
16	81.7	-4.3%	-10.9%

3000K | Rf: 88.1 | Rg: 99.7

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	87.7	-5.9%	-0.3%
2	87.9	-4.4%	4.3%
3	82.9	-1.2%	7.9%
4	89.9	0.6%	4.7%
5	92.7	3.0%	3.5%
6	92.7	3.6%	-1.7%
7	90.8	-1.3%	-4.4%
8	93.7	-2.5%	-2.2%
9	91.7	-3.7%	2.3%
10	85.5	-2.8%	7.8%
11	83.3	0.7%	11.0%
12	86.4	5.5%	3.8%
13	90.6	4.6%	-3.6%
14	85.6	5.9%	-8.4%
15	89.5	-0.6%	-5.7%
16	82.6	-2.7%	-12.0%

3500K | Rf: 86.1 | Rg: 95.5

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	86.6	-4.2%	3.4%
2	91.7	-1.4%	1.8%
3	94.9	-0.7%	0.4%
4	87.9	-4.5%	-4.1%
5	85.9	-10.3%	-2.7%
6	89.8	-5.2%	-0.4%
7	79.6	-9.5%	6.5%
8	87.6	-4.0%	5.7%
9	81.4	-0.5%	11.8%
10	78.3	3.3%	11.4%
11	85.7	6.3%	6.1%
12	86.3	7.1%	-4.6%
13	86.1	-0.7%	-9.6%
14	85.1	0.8%	-10.4%
15	83.4	-4.1%	-5.3%
16	82.5	-3.6%	-5.7%

4000K | Rf: 87.6 | Rg: 96.8

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	89.0	-3.1%	2.1%
2	93.2	-0.9%	1.3%
3	94.3	-1.1%	0.7%
4	89.5	-4.0%	-2.3%
5	87.6	-7.8%	-1.8%
6	92.2	-4.6%	0.1%
7	87.4	-6.6%	3.6%
8	85.7	-3.8%	7.0%
9	81.5	-1.3%	12.4%
10	80.0	0.9%	11.4%
11	83.3	5.9%	8.7%
12	89.7	4.8%	-0.3%
13	88.5	2.4%	-6.3%
14	92.7	4.0%	-3.8%
15	86.1	-1.6%	-4.5%
16	85.0	-1.4%	-5.0%

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------


TM30 DATA

LED SUSPENSION DOWNLIGHT WITH REMOTE POWER - END FEED

TM-30-15 DATA: The data below is for SS2C, SS5C, SS7C, and SS10C bare LED Soft Strips. Consistent color temperatures throughout a single strip and among multiple strips is possible through a 3 phase binning process in which each order is inspected with a color meter to ensure uniformity.

2700D | Rf: 89.5 | Rg: 100.8

Color Vector Graphic




■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	88.8	-5.1%	1.4%
2	89.8	-2.7%	4.1%
3	87.2	0.3%	5.9%
4	92.3	-0.9%	1.0%
5	93.3	1.5%	1.7%
6	92.4	3.6%	-0.2%
7	92.2	-0.9%	-2.4%
8	96.7	-0.4%	-1.1%
9	92.3	-1.2%	3.7%
10	88.9	-0.0%	6.1%
11	86.4	5.1%	7.4%
12	88.2	6.3%	-0.9%
13	87.2	3.8%	-8.1%
14	84.2	3.8%	-11.0%
15	89.8	-2.6%	-4.3%
16	82.7	-3.4%	-11.1%

3000D | Rf: 89.8 | Rg: 101.4

Color Vector Graphic



■ Test ■ Reference

HUE BIN	Rf	GRAPHIC SHIFTS %	
		CHROMA	HUE
1	90.2	-4.2%	1.5%
2	90.9	-2.0%	3.7%
3	87.9	0.8%	5.5%
4	92.1	-0.9%	0.6%
5	93.0	1.5%	1.6%
6	92.2	3.9%	-0.2%
7	92.1	-0.3%	-2.0%
8	96.7	0.0%	-1.2%
9	92.5	-0.6%	3.7%
10	88.3	1.1%	7.0%
11	87.2	4.1%	7.4%
12	87.2	6.7%	-1.0%
13	88.2	3.8%	-7.2%
14	85.3	4.3%	-9.9%
15	90.9	-2.2%	-3.6%
16	83.4	-2.2%	-11.2%

PROJECT	FIXTURE TYPE	DATE
---------	--------------	------